

Sample image

Datasheet

Article number: 70014865

Description: Other Component

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107						
定格絶縁電圧 Ui						
			電圧 (V) AC / DC			
			690 AC / DC			
定格連続通電電流 Iu/Ith						
Current (A)		周囲温度 (°C)		ピーク温度 (°C) 追加要求事項		
20		55		60 周囲温度 +55°C、24 時間、ただし 瞬時ピーク温度 +60°C		
定格操作電流 Ie						
負荷種別			電圧 (V)		Current (A)	
AC-15			220 - 240		6	
AC-15			380 - 440		4	
定格操作電力						
負荷種別		電圧 (V)		相数		極数 電力 (kW)
AC-3		220 - 240		3		3
AC-3		380 - 440		3		5,50
AC-3		660 - 690		3		5,50
AC-3		220 - 240		1		2,20
AC-3		380 - 440		1		3
AC-23A		220 - 240		3		3,70
AC-23A		380 - 440		3		7,50
AC-23A		660 - 690		3		7,50
AC-23A		220 - 240		1		2,50
AC-23A		380 - 440		1		3,70
最大ヒューズ定格 IEC						
ヒューズ特性			ヒューズ数		Current (A)	
gG			1		25	
UL60947-4-1, UL508						
Nominal Voltage						
			電圧 (V) AC / DC			
			600 AC			
定格絶縁電圧 Ui						
			電圧 (V) AC / DC			
			600 AC			
定格熱電流						
Current (A)			周囲温度 (°C) 備考			
20			0 - 40 --			
Horsepower rating						
Across-the-Line Motor Starting		電圧 (V)		相数		極数 Power (HP) Ambient temperature [°C]
DOL		110 - 120		1		2 0,50 40
DOL		220 - 240		1		2 1 40
DOL		277 - 277		1		2 2 40
DOL		440 - 480		1		2 2 40
DOL		550 - 600		1		2 2 40
DOL		110 - 120		3		3 1,50 40
DOL		220 - 240		3		3 3 40
DOL		440 - 480		3		3 5 40
DOL		550 - 600		3		3 5 40
Pilot duty rating code						
Duty Code						
A600						
SCCR / Max. fuse rating						
Conditions of acceptability						
These devices are suitable for use on circuits capable of delivering not more than 5kA rms symmetrical amperes, 600V ac max. when protected by Class RK1 fuses.						
Temp. rating of wire						
Temperature rating (°C)			Current (A) Text			
60 - 75			-- Use copper wire only			
General Use						
AC / DC		電圧 (V)		Current (A)		相数 極数 No. of contacts in series
AC		277		20		1 1 1
AC		600		20		1 2 1

General Use					
AC / DC	電圧 (V)	Current (A)	相数	極数	No. of contacts in series
AC	600	20	3	3	1
CSA					
Nominal Voltage					
			電圧 (V) AC / DC		
			600 AC		
定格絶縁電圧 Ui					
			電圧 (V) AC / DC		
			600 AC		
定格熱電流					
		Current (A)	周囲温度 (°C) 備考		
		20	0 - 40 --		
Horsepower rating					
Across-the-Line Motor Starting		電圧 (V)	相数	極数	Power (HP)
DOL		110 - 120	1	2	0,50
DOL		220 - 240	1	2	1
DOL		277 - 277	1	2	2
DOL		440 - 480	1	2	2
DOL		550 - 600	1	2	2
DOL		110 - 120	3	3	1,50
DOL		220 - 240	3	3	3
DOL		440 - 480	3	3	5
DOL		550 - 600	3	3	5
Pilot duty rating code					
Duty Code					
A600					
Temp. rating of wire					
		Temperature rating (°C)	Current (A) Text		
		75	-- --		
General Use					
AC / DC	電圧 (V)	Current (A)	相数	極数	No. of contacts in series
AC	277	20	1	1	1
AC	600	20	1	2	1
AC	600	20	3	3	1
GENERAL TECHNICAL INFORMATION					
端子ネジ締付トルク					
			締付トルク (Nm)	締付トルク (lb-in)	
			1	9	
Stripping length					
			Length (mm) --		
			9 STRIPPINGLENGTH		
電線サイズ					
電線種別	最小値 / 最大値		1端子当たりの配線数	断面積 (mm²) or (AWG/kcmil)	電線材料
単線	最小		1	0.75mm²	銅
単線	最小		2	0.75mm²	銅
細撚線	最小		1	0.75mm²	銅
細撚線	最小		2	0.75mm²	銅
細撚線	最大		2	AWG 12	銅
細撚線	最大		2	2.5mm²	銅
単線または荒撚線	最大		2	AWG 10	銅
単線または荒撚線	最大		2	4mm²	銅
DIN46228規格フェール適用の細撚線	最小		1	0.75mm²	銅
DIN46228規格フェール適用の細撚線	最小		2	0.75mm²	銅
DIN46228規格フェール適用の細撚線	最大		2	2.5mm²	銅
認証					
仕様					
マーキング					
EAC					
CEマーキング					
UK Directives					
CSA C.22.2 No.14					
GB/T14048.3					
Recommended screw driver					
Type of screw driver			Value		
Cross Screwdriver			PH1		
Slot screwdriver according to DIN 5264			0,8x4		
注意事項					
備考					
- 接点に潤滑剤を塗布したり、表面処理をしたりしないでください。					

注意事項

備考

- スイッチの取り付け、接続、操作の設定は、技術的に認められた規則に従って、有資格者のみが行うことができます。
- 銅線のみを使用してください。電線を半田付けしないでください。
- ジャンパー線(コモン線)に接続された端子ネジは工場出荷時には仮締め状態となっています。ジャンパー線(コモン線)に接続された端子ネジの締め付けを含む全ての端子ネジが、必ず適切なトルクで締められていることをご確認の上、ご使用ください。
- スイッチの設置後、端子間の間隔は、適用される規格の要件を満たすのに十分なものでなければなりません。

Waste Electrical & Electronic Equipment (WEEE)

Picture name	Description
	Do not throw in the trash as care must be taken to ensure environmentally sound disposal and recycling. Please either use an environmentally friendly waste disposal company; return to the supplier for disposal; or return direct to the manufacturer, Kraus & Naimer. You can find local Kraus & Naimer offices at www.krausnaimer.com

Proposition 65


Picture name	Description
	WARNING: This product can expose you to chemicals including nickel and lead, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov .

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

Mounting-EF




IP - Code front side		IP66, IP67, IP69k
Stages		1,00 - 12,00
A	□	36,00 mm
B	∅	5,00 mm
C	∅	15,00 - 19,00 mm
D	H	<= 4,00 mm
E	H	48,00 mm
F	H	59,00 mm
G	H	6,70 mm
M	M̂	0,50 Nm
M1	M̂	0,90 Nm





Wiring diagram

CH10.A250.EF



Switch program


CH10.A250.EF

 Kraus & Naimer		CH10		A250		Page 1 of 1							
Face Plate													
		1	3	5	7	9	11	13	15	17	19	21	23
													
Switching Angle 60 Total switching Angle 120		2	4	6	8	10	12	14	16	18	20	22	24
1	270	■				■							
	285												
	300												
	315												
	2	330		■				■					
		345											
		0											
	3	15											
		30			■	■							
		45											
		60											
		75											
		90											
		105											
	120												
	135												
	150												
165													
180													
195													
210													
225													
240													
255													

Version: 8

Face plate

S0.F076/A1B.PEL



HANDLES

Designation: S0C.G251
Handle colour: "1" black

