



Sample image

Datasheet

Article number: 70015316

Description: Other Component

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107						
Номинальное напряжение изоляции Ui						
Напряжение (В) Переменный ток/Постоянный ток						
690 AC / DC						
Номинальный длительный ток Iu/Ith						
Сила тока (А)	Температура окружающей среды (°C)	Пиковое значение температуры (°C)	Дополнительные требования			
20	55	60	Средняя температура окружающей среды +55°C в течение 24 часов с максимальным значением +60°C			
Номинальный рабочий ток Ie						
Категория применения			Напряжение (диапазон) (В)		Сила тока (А)	
AC-15			220 - 240		6	
AC-15			380 - 440		4	
Номинальная рабочая мощность						
Категория применения		Напряжение (диапазон) (В)		Количество фаз	Количество полюсов	Мощность (кВт)
AC-3		220 - 240		3	3	3
AC-3		380 - 440		3	3	5,50
AC-3		660 - 690		3	3	5,50
AC-3		220 - 240		1	2	2,20
AC-3		380 - 440		1	2	3
AC-23A		220 - 240		3	3	3,70
AC-23A		380 - 440		3	3	7,50
AC-23A		660 - 690		3	3	7,50
AC-23A		220 - 240		1	2	2,50
AC-23A		380 - 440		1	2	3,70
Максимальный номинал предохранителя по IEC						
Характеристика предохранителя				Количество предохранителей		Сила тока (А)
gG				1		25
UL60947-4-1 , UL508						
Nominal Voltage						
Voltage (V) AC / DC						
600 AC						
Номинальное напряжение изоляции Ui						
Напряжение (В) Переменный ток/Постоянный ток						
600 AC						
Rated thermal current						
Current (A)		Ambient temperature (°C) Additional Text				
20		0 - 40 --				
Horsepower rating						
Across-the-Line Motor Starting				Voltage (V)	No. of phases	No. of poles
DOL				110 - 120	1	2
DOL				220 - 240	1	2
DOL				277 - 277	1	2
DOL				440 - 480	1	2
DOL				550 - 600	1	2
DOL				110 - 120	3	3
DOL				220 - 240	3	3
DOL				440 - 480	3	3
DOL				550 - 600	3	3
Pilot duty rating code						
Duty Code						
A600						
SCCR / Max. fuse rating						
Conditions of acceptability						
These devices are suitable for use on circuits capable of delivering not more than 5kA rms symmetrical amperes, 600V ac max. when protected by Class RK1 fuses.						
Temp. rating of wire						
Temperature rating (°C)				Current (A) Text		
60 - 75				-- Use copper wire only		
General Use						
AC / DC	Voltage (V)	Current (A)	No. of phases	No. of poles	No. of contacts in series	
AC	277	20	1	1	1	



Kraus & Naimer

General Use					
AC / DC	Voltage (V)	Current (A)	No. of phases	No. of poles	No. of contacts in series
AC	600	20	1	2	1
AC	600	20	3	3	1

CSA

Nominal Voltage	1.2 V
-----------------	-------

	Voltage (V)	AC / DC
	600	AC

Номинальное напряжение изоляции U_i	
---------------------------------------	--

Напряжение (В)	Переменный ток/Постоянный ток
600 AC	

Rated thermal current	100 A
-----------------------	-------

Current (A)	Ambient temperature (°C)	Additional Text
20	0 - 40	--

Horsepower rating

Across-the-Line Motor Starting	Voltage (V)	No. of phases	No. of poles	Power (HP)	Ambient temperature [°C]
DOL	110 - 120	1	2	0,50	40
DOL	220 - 240	1	2	1	40
DOL	277 - 277	1	2	2	40
DOL	440 - 480	1	2	2	40
DOL	550 - 600	1	2	2	40
DOL	110 - 120	3	3	1,50	40
DOL	220 - 240	3	3	3	40
DOL	440 - 480	3	3	5	40
DOL	550 - 600	3	3	5	40

Pilot duty rating code

Duty Code
A600

Temp. rating of wire

Temperature rating (°C)	Current (A)	Text
75	--	--

General Use

AC / DC	Voltage (V)	Current (A)	No. of phases	No. of poles	No. of contacts in series
AC	277	20	1	1	1
AC	600	20	1	2	1
AC	600	20	3	3	1

ОСНОВНАЯ ТЕХНИЧЕСКАЯ ИНФОРМАЦИЯ

Момент затяжки винтов

Момент затяжки (Нм)	Момент затяжки (фунт-дюйм)
1	9

Stripping length

	Length (mm) --
	9 STRIPPINGLENGTH

Size of conductor	
-------------------	--

composition of conductor	Min. / Max. value	No. of conductor per terminal	Cross section (mm ²) or (AWG/kcmil)	Material of the wire
solid wire	Min.	1	0,75mm ²	Copper
solid wire	Min.	2	0,75mm ²	Copper
flexible wire	Min.	1	0,75mm ²	Copper
flexible wire	Min.	2	0,75mm ²	Copper
flexible wire	Max.	2	AWG 12	Copper
flexible wire	Max.	2	2,5mm ²	Copper
Single-core or stranded wire	Max.	2	AWG 10	Copper
Single-core or stranded wire	Max.	2	4mm ²	Copper
flexible wire with ferrule according to DIN 46228	Min.	1	0,75mm ²	Copper
flexible wire with ferrule according to DIN 46228	Min.	2	0,75mm ²	Copper
flexible wire with ferrule according to DIN 46228	Max.	2	2,5mm ²	Copper

Approbations

Specification	Marking
---------------	---------

EAC

CE marking

UK Directives

CSA C.22.2 No.14

GB/T14048.3

Marking



Рекомендуемая отвертка

Тип отвертки	Value
Крестовая отвёртка	PH1
Slot screwdriver according to DIN 5264	0,8x4

Общая информация

Текст

- Не смазывайте и не разбирайте контакты.

Общая информация

Текст

- Переключатели могут быть установлены, подключены и введены в эксплуатацию только квалифицированным персоналом в соответствии с принятыми техническими правилами.
- Используйте только медные провода. Не покрывать конец провода оловом.
- Клеммы с заводскими перемычками затянуты в процессе производства. Во время откручивания скреплённых перемычками клемм проследите, что бы перемычки не потерялись. После подключения все винты клемм должны быть затянуты с рекомендуемым моментом затяжки винта.
- После установки переключателей расстояния между клеммами должны быть достаточными для выполнения требований применимых стандартов.

Waste Electrical & Electronic Equipment (WEEE)

Picture name	Description
	Do not throw in the trash as care must be taken to ensure environmentally sound disposal and recycling. Please either use an environmentally friendly waste disposal company; return to the supplier for disposal; or return direct to the manufacturer, Kraus & Naimer. You can find local Kraus & Naimer offices at www.krausnaimer.com

Proposition 65

Picture name	Description
	WARNING: This product can expose you to chemicals including nickel and lead, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov .

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

Mounting-FT2




IP - Код лицевая сторона		IP66, IP67, IP69k
Stages		1,00 - 12,00
A	H	3,20 mm
A+_tol.	H	0,20 mm
A-_tol.	H	0,00 mm
B	H	24,10 mm
B+_tol.	H	0,40 mm
B-_tol.	H	0,00 mm
C	Ø	22,30 mm
C+_tol.	Ø	0,40 mm
C-_tol.	Ø	0,00 mm
D	H	<= 6,00 mm
E	□	48,00 mm
M	↺	0,50 Nm
M1	↺	1,80 Nm



Wiring diagram

CH10.A476.FT2





Switch program

CH10.A476.FT2



Kraus & Naimer


CH10
A476
Page 1 of 1

Face Plate														
														
		1	3	5	7	9	11	13	15	17	19	21	23	
Switching Angle 60 Total switching Angle 120														
		2	4	6	8	10	12	14	16	18	20	22	24	
1	270													
	285													
	300													
	315													
	2	330												
		345												
		0												
		15												
	3	30												
		45												
		60												
		75												
		90												
		105												
		120												
		135												
		150												
165														
180														
195														
210														
225														
240														
255														

Version: 59

Face plate

S0.F076/A10.E1L



HANDLES

Designation: S0C.G251

Handle colour: "1" black

