

Sample image

Datasheet

Article number: 70011686

Designation: CH10.A220.EF

Description: Switch

IEC 60947-3 EN 60947-3, VDE 0660 Teil 107						
Märkdraftspänning Ui						
Spänning (V) AC / DC						
690 AC / DC						
Märkdraftström vid konstant drift						
Ström (A)		Omgivningstemperatur (°C)		Temperatur topp (°C) ytterligare krav		
20		55		60 Omginingstemperatur +55°C under 24 timmar med toppar upp till +60°C		
Märkdraftström Ie						
Urvals kriterie				Spänning (V)		Ström (A)
AC-15				220 - 240		6
AC-15				380 - 440		4
Märkdrafteffekt						
Urvals kriterie		Spänning (V)		No. of phases		No. of poles
AC-3		220 - 240		3		3
AC-3		380 - 440		3		5,50
AC-3		660 - 690		3		5,50
AC-3		220 - 240		1		2,20
AC-3		380 - 440		1		3
AC-23A		220 - 240		3		3,70
AC-23A		380 - 440		3		7,50
AC-23A		660 - 690		3		7,50
AC-23A		220 - 240		1		2,50
AC-23A		380 - 440		1		3,70
Max försäkring, IEC						
Säkringskarakteristik				Antal säkringar		Ström (A)
gG				1		25
UL60947-4-1 , UL508						
Nominal Voltage						
Spänning (V) AC / DC						
600 AC						
Märkdraftspänning Ui						
Spänning (V) AC / DC						
600 AC						
Rated thermal current						
Ström (A)		Omgivningstemperatur (°C) Additional Text				
20		0 - 40 --				
Horsepower rating						
Across-the-Line Motor Starting		Spänning (V)		No. of phases	No. of poles	Power (HP)
DOL		110 - 120		1	2	0,50
DOL		220 - 240		1	2	1
DOL		277 - 277		1	2	2
DOL		440 - 480		1	2	2
DOL		550 - 600		1	2	2
DOL		110 - 120		3	3	1,50
DOL		220 - 240		3	3	3
DOL		440 - 480		3	3	5
DOL		550 - 600		3	3	5
Pilot duty rating code						
Duty Code						
A600						
SCCR / Max. fuse rating						
Conditions of acceptability						
These devices are suitable for use on circuits capable of delivering not more than 5kA rms symmetrical amperes, 600V ac max. when protected by Class RK1 fuses.						
Temp. rating of wire						
Temperature rating (°C)				Ström (A) Text		
60 - 75				-- Use copper wire only		
General Use						
AC / DC	Spänning (V)	Ström (A)	No. of phases	No. of poles	No. of contacts in series	
AC	277	20	1	1	1	
AC	600	20	1	2	1	

General Use						
AC / DC	Spänning (V)	Ström (A)	No. of phases	No. of poles	No. of contacts in series	
AC	600	20	3	3	1	
CSA						
Nominal Voltage						
				Spänning (V)	AC / DC	
				600	AC	
Märkdriftspänning Ui						
				Spänning (V)	AC / DC	
				600	AC	
Rated thermal current						
		Ström (A)	Omgivningstemperatur (°C)		Additional Text	
		20	0 - 40		--	
Horsepower rating						
Across-the-Line Motor Starting			Spänning (V)	No. of phases	No. of poles	Power (HP)
DOL			110 - 120	1	2	0,50
DOL			220 - 240	1	2	1
DOL			277 - 277	1	2	2
DOL			440 - 480	1	2	2
DOL			550 - 600	1	2	2
DOL			110 - 120	3	3	1,50
DOL			220 - 240	3	3	3
DOL			440 - 480	3	3	5
DOL			550 - 600	3	3	5
Pilot duty rating code						
Duty Code						
A600						
Temp. rating of wire						
			Temperature rating (°C)	Ström (A) Text		
			75	-- --		
General Use						
AC / DC	Spänning (V)	Ström (A)	No. of phases	No. of poles	No. of contacts in series	
AC	277	20	1	1	1	
AC	600	20	1	2	1	
AC	600	20	3	3	1	
GENERAL TECHNICAL INFORMATION						
Tightening torque of screws						
				tightening torque (Nm)	tightening torque (lb-in)	
				1	9	
Stripping length						
				Length (mm) --		
				9 STRIPPINGLENGTH		
Size of conductor						
composition of conductor	Min. / Max. value	No. of conductor per terminal		Cross section (mm²) or (AWG/kcmil)	Material of the wire	
solid wire	Min.	1		0,75mm²	Copper	
solid wire	Min.	2		0,75mm²	Copper	
flexible wire	Min.	1		0,75mm²	Copper	
flexible wire	Min.	2		0,75mm²	Copper	
flexible wire	Max.	2		AWG 12	Copper	
flexible wire	Max.	2		2,5mm²	Copper	
Single-core or stranded wire	Max.	2		AWG 10	Copper	
Single-core or stranded wire	Max.	2		4mm²	Copper	
flexible wire with ferrule according to DIN 46228	Min.	1		0,75mm²	Copper	
flexible wire with ferrule according to DIN 46228	Min.	2		0,75mm²	Copper	
flexible wire with ferrule according to DIN 46228	Max.	2		2,5mm²	Copper	
Approbations						
Specification				Marking		
EAC						
CE marking						
UK Directives						
CSA C.22.2 No.14						
GB/T14048.3						
Rekomenderad skruvmejsel						
Typ av skruvmejsel				Value		
Stjärnskruvmejsel				PH1		
Slot screwdriver according to DIN 5264				0,8x4		
General Information						
Text						
- Smörjning och behandling av kontakterna är förbjuden.						

General Information

Text

- Inkoppling och service av strömställaren får endast utföras av behörig personal. Strömställaren är underhållsfri.
- Använd endast kopparkabel. Kabeln får inte förtennas.
- Alla anslutningsskruvar måste dras med rekommenderat moment, även de som inte används då det kan finnas interna överkopplingar.
- Vid installation av strömställaren skall kontrolleras att kryp- och luftavstånd motsvarar gällande föreskrifter.

Waste Electrical & Electronic Equipment (WEEE)

Picture name

Description



Do not throw in the trash as care must be taken to ensure environmentally sound disposal and recycling. Please either use an environmentally friendly waste disposal company; return to the supplier for disposal; or return direct to the manufacturer, Kraus & Naimer. You can find local Kraus & Naimer offices at www.krausnaimer.com

Proposition 65

Picture name

Description




WARNING: This product can expose you to chemicals including nickel and lead, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Classification Contact: Rigid contact bridge

Classification Contact Mat: Silver

Classification Terminal: Screw terminal

Mounting-EF



Skyddsklass frontpanel, IP IP66, IP67, IP69k

Stages 1,00 - 12,00

A □ 36,00 mm

B Ø 5,00 mm

C Ø 15,00 - 19,00 mm

D H <= 4,00 mm

E H 48,00 mm

F H 59,00 mm

G H 6,70 mm

M ⚙ 0,50 Nm

M1 ⚙ 0,90 Nm

Wiring diagram

CH10.A220.EF




Switch program

CH10.A220.EF



Kraus & Naimer


CH10
A220
Page 1 of 1

Face Plate																										
		1		3		5		7		9		11		13		15		17		19		21		23		
Switching Angle 60 Total switching Angle 60		2		4		6		8		10		12		14		16		18		20		22		24		
1	330																									
	345																									
	0																									
	15																									
	2	30																								
		45																								
		60																								
		75																								
		90																								
		105																								
		120																								
		135																								
		150																								
		165																								
	180																									
	195																									
	210																									
225																										
240																										
255																										
270																										
285																										
300																										
315																										

Version: 106

Face plate

S0.F072/A1B.PEL



HANDLES

Designation: S0C.G251

Handle colour: "1" black

