

## Blacklight BL368 Linear T8 F15W T8 BL368 0000082



#### **Product features**

The energy distribution of the BL368 lamp is concentrated around the spectral peak at 368nm which is the most important frequency for the attraction of flying insects.













### PRODUCT OVERVIEW

Product name	F15W T8 BL368
Technology	Special applications
Туре	Т8
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	SPG
E-number FI	4940737
Light colour	BL368 Blacklight
Product Voltage (V)	55
Dimmable	No
Dimming method	N/A
Average life (Nominal) (h)	14000
Product EAN number	5410288000824

#### **DATA TABLE**

General data	
Product name	F15W T8 BL368
Technology	Special applications
Туре	T8
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	SPG
Operating temperature range (°C)	-15°C+40°C
E-number FI	4940737
Optical data	
Ambient temperature for maximum luminous flux (°C)	25
Light colour	BL368 Blacklight




# Blacklight BL368 Linear T8 F15W T8 BL368 0000082

Valles and letter of the season and office	
Adjustable chromaticity	N
lectrical data	
Watt (Rated) - High frequency (W)	13.50
Current (A)	0.310
Mains voltage (V)	230-240V
Product Voltage (V)	55
Control gear required	Yes
Fransformer required	No
Dimmable	No
Dimming method	N/A
ifetime data	
Average life (Nominal) (h)	14000
hysical data	
Nominal Product Length (mm)	450.0
Nominal Product Diameter (mm)	26
Max. Length base to base (mm) - A	437.4
ength base to pin Min-Max (mm) - B	442.1-444.5
Max. Lamp Length (mm) - C/L	451.6
Max. Lamp Diameter (mm) - D	28.0
Veight (kg)	0.063
ackaging	
Single packaging type	Carton
Product EAN number	5410288000824
Packaging single length / height (cm)	45.2
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.8
Jnits per outer package	25
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	15.0
afety data	
amp mercury content (mg)	9.0
Optimal operating condition (°C)	-15-40
spanial operating continuon ( O)	Applicable
Breakage cleaning instructions	, tpp noable
	Applicable
Breakage cleaning instructions Recommendation for disposal at end of ife	
Breakage cleaning instructions Recommendation for disposal at end of	Applicable

### **PHOTOMETRY**



# Blacklight BL368 Linear T8 F15W T8 BL368 0000082



### **TECHNICAL DRAWINGS**

