


Blacklight BL368 Toughcoat T12
F20W T12 BL368 24 Toughcoat™
0000125



Product features

- Excellent fragment retention in the event of breakageThe protective FEP coating meets the IEC60068-2-75 Pendulum Hammer test (5 Joule) and the 4m drop test, demonstrating excellent glass retention in the event of accidental lamp breakageThe 97% UV-A transmission of FEP maintains maximum insect attraction



PRODUCT OVERVIEW

Product name	F20W T12 BL368 24 Toughcoat™
Technology	Special applications
Type	T12
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	SPG
E-number FI	4940431
Light colour	BL368 Blacklight
Dimmable	No
Dimming method	N/A
Average life (Nominal) (h)	10000
Product EAN number	5410288001258

DATA TABLE

General data	
Product name	F20W T12 BL368 24 Toughcoat™
Technology	Special applications
Type	T12
Cap/Base	G13
Lamp finish	Frosted/Coated
Fixture rating	Enclosed
General application	SPG
Operating temperature range (°C)	-20°C...+40°C
E-number FI	4940431
Optical data	
Ambient temperature for maximum luminous flux (°C)	25
Light colour	BL368 Blacklight
Adjustable chromaticity	N
Electrical data	

Blacklight BL368 Toughcoat T12

F20W T12 BL368 24 Toughcoat™
0000125

Watt (Rated) - High frequency (W)	13.50
Mains voltage (V)	230-240V
Control gear required	Yes
Transformer required	No
Dimmable	No
Dimming method	N/A

Lifetime data

Average life (Nominal) (h)	10000
----------------------------	-------

Physical data

Nominal Product Length (mm)	600.0
Nominal Product Diameter (mm)	38
Max. Length base to base (mm) - A	589.8
Length base to pin Min-Max (mm) - B	594.5-596.9
Max. Lamp Length (mm) - C/L	604.0
Max. Lamp Diameter (mm) - D	40.5
Weight (kg)	0.201

Packaging

Single packaging type	Carton
Product EAN number	5410288001258
Packaging single length / height (cm)	60.3
Packaging single width (cm)	4.3
Packaging single depth (cm)	4.1
Units per outer package	25
Packaging outer width (cm)	22.0
Packaging outer depth (cm)	21.0

Safety data

Lamp mercury content (mg)	9.00
Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	Yes
Intended purpose	Flykilling - Insect attraction
Safety message	Not suitable for household

PHOTOMETRY

