

Start Spot Aluminium IP65
START SPOT ALUMINIUM 740LM 830 IP65 WHT
0005174



- Product features**
- Integrated LED recessed spotlight, white bezel colour, white reflector, 740lm, 9.0W, dimmable trailing/leading edge, 3000K, 40° degree beam angle, polycarbonate and aluminium body, low profile 62mm recessed depth, IP65 from the front, IK03, loop-in/loop-out terminals for fast wiring, weight 0,165Kg, 85mm bezel diameter, 68-72mm cutout, clear lens.

PRODUCT OVERVIEW

Product name	START SPOT ALUMINIUM 740LM 830 IP65 WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Residential & Consumer
Warranty	3 years
Fixture luminous flux (lm)	740
Luminaire efficacy (lm/W)	82
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	40
Photobiological Risk Group	RG1
Total power consumption (W)	9
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Minimum dimming level (%)	10
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65/20
IK rating	IK03
Product EAN number	5410288051741

DATA TABLE

General data	
Product name	START SPOT ALUMINIUM 740LM 830 IP65 WHT
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Residential & Consumer

Start Spot Aluminium IP65

START SPOT ALUMINIUM 740LM 830 IP65 WHT

0005174

Operating temperature range (°C)	-10°C...+35°C
Performance ambient temperature Tq (°C)	25
Warranty	3 years

Optical data

Fixture luminous flux (lm)	740
Luminaire efficacy (lm/W)	82
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	40
Distribution type	Symmetric
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	9
Mains voltage (V)	220-240V
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	40
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Minimum dimming level (%)	10
Inrush Current (A)	10
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	F
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 13A C Breaker	65
Max. Luminaires per 16A B Breaker	30

Lifetime data

Lifespan L70 B50	47000
------------------	-------

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65/20
IK rating	IK03
Diffuser finish	Other
Diffuser material	None
Reflector finish	White
Nominal Product Diameter (mm)	86
Cutout Dimensions (W x L in mm or Diameter in mm)	68-72

Start Spot Aluminium IP65

START SPOT ALUMINIUM 740LM 830 IP65 WHT

0005174

Weight (kg)	0.14
Recessed Depth (mm)	100

Packaging

Single packaging type	Carton
Product EAN number	5410288051741
Packaging single length / height (cm)	10.0
Packaging single width (cm)	10.0
Packaging single depth (cm)	8.5
DUN14 (inner)	25410288051745
Units per inner package	6
Packaging inner length / height (cm)	28.5
Packaging inner width (cm)	9.0
Units per outer package	36
Packaging outer width (cm)	35.6
Packaging outer depth (cm)	29.3

Safety data

Optimal operating condition (°C)	-10-35
----------------------------------	--------

PHOTOMETRY

TECHNICAL DRAWINGS
