



Product features

Instant illumination, - Excellent colour rendering, - Sparkling light output, - Transformer free operation,
 Average life 1500hours, - Suitable for outdoor floodlighting/security lighting, - Suitable for interior floodlighting, uplighting and wall washing.



PRODUCT OVERVIEW

Product name	DE 78MM ECO 230V 80W R7S BL
Technology	Halogen
Watt (Rated) (W)	80



Туре	Halogen
Cap/Base	R7s
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Warranty	2 years
Luminous flux (lm)	1395
Colour temperature (K)	2900
Light colour	Homelight
Colour Variation Initial (SDCM)	N/A
Photobiological Risk Group	Not applicable
Product Voltage (V)	230
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Average life (Nominal) (h)	1500
Product EAN number	5410288225746


DATA TABLE

General data	
Product name	DE 78MM ECO 230V 80W R7S BL
Technology	Halogen
Watt (Rated) (W)	80
Туре	Halogen
Cap/Base	R7s
Lamp finish	Clear
Fixture rating	Enclosed
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
Warranty	2 years
Optical data	
·	
Luminous flux (Im)	1395
Luminous flux (Rated) (Im)	1395
Colour temperature (K)	2900
Light colour	Homelight
Colour Variation Initial (SDCM)	N/A
Adjustable chromaticity	N
Photobiological Risk Group	Not applicable
Electrical data	
Equivalent watt (W)	100
Starting time (max) (s)	0.01
Mains voltage (V)	230V
Product Voltage (V)	230
Lamp power factor	1
Control gear required	No
Transformer required	No



Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	80
Lifetime data	
Average life (Nominal) (h)	1500
Average life (Rated) (h)	1500
Physical data	
Nominal Product Length (mm)	80.3
Nominal Product Diameter (mm)	12
Max. Lamp Length (mm) - C/L	81.0
Max. Lamp Diameter (mm) - D	12
Weight (kg)	0.005
Packaging	
Packaging Single packaging type	Mix blister(20% carton, 80% pl
	Mix blister(20% carton, 80% pl 5410288225746
Single packaging type	, ,
Single packaging type Product EAN number	5410288225746
Single packaging type Product EAN number Packaging single length / height (cm)	5410288225746 14.0
Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	5410288225746 14.0 12.0
Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	5410288225746 14.0 12.0 1.2
Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) Units per outer package	5410288225746 14.0 12.0 1.2
Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm) Packaging outer depth (cm)	5410288225746 14.0 12.0 1.2 10 14.5
Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm)	5410288225746 14.0 12.0 1.2 10 14.5
Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm) Packaging outer depth (cm)	5410288225746 14.0 12.0 1.2 10 14.5
Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm) Packaging outer depth (cm) Safety data	5410288225746 14.0 12.0 1.2 10 14.5
Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm) Packaging outer depth (cm) Safety data Breakage cleaning instructions Recommendation for disposal at end of	5410288225746 14.0 12.0 1.2 10 14.5 12.4

PHOTOMETRY



TECHNICAL DRAWINGS





