

RefLED R80 V3 806LM 830 E27 SL 0028413



Product features

Energy efficient LED alternative for traditional incandescent and halogen blown reflector lamps
Modern construction and attractive designs Mercury free solutions Long average rated lifetime: 15,000
hours Lower maintenance cost compared to traditional lamps Non-dimmables 3 years warrantys
Perfect for general lighting applications: residential lighting, down lights, hotels, hotels, restaurants,
bars, lobbies, corridors, halls, etc



PRODUCT OVERVIEW

Product name	REFLED R80 V3 806LM 830 E27 SL
Technology	LED
Watt (Rated) (W)	9
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
E-number FI	4740803
Warranty	3 years
Colour temperature (K)	3000
Light colour	Warm White
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288284132

DATA TABLE

General data	
Product name	REFLED R80 V3 806LM 830 E27 SL
Technology	LED
Watt (Rated) (W)	9
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
E-number FI	4740803
Warranty	3 years
Optical data	
Colour temperature (K)	3000



RefLED R80 REFLED R80 V3 806LM 830 E27 SL 0028413

Light colour	Warm White
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	198
Beam Angle (°)	120
Electrical data	
Starting time (max) (s)	0.5
Product Voltage (V)	230
Lamp power factor	0.5
Dimmable	No
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
. , , , ,	
Physical data	
Nominal Product Length (mm)	114
Nominal Product Diameter (mm)	81
Weight (kg)	0.15
Packaging	
Single packaging type	Carton
Product EAN number	5410288284132
Packaging single length / height (cm)	4.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	7.8
Units per outer package	6
Packaging outer width (cm)	17.0
Packaging outer depth (cm)	12.5
Safety data	
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures