

RefLED R50
REFLED R50 V3 470LM 865 E14 SL
0026335



- Product features**
- Energy efficient LED alternative for traditional incandescent and halogen blown reflector lamp• Modern construction and attractive design• Mercury free solution• Long average rated lifetime: 15,000 hours• Lower maintenance cost compared to traditional lamps• Non-dimmable• 3 years warranty• Perfect for general lighting applications: residential lighting, down lights, hotels, hotels, restaurants, bars, lobbies, corridors, halls, etc



PRODUCT OVERVIEW

Product name	REFLED R50 V3 470LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
E-number FI	4740800
Warranty	3 years
Colour temperature (K)	6500
Light colour	Daylight
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Beam Angle (°)	120
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288263359

DATA TABLE

General data	
Product name	REFLED R50 V3 470LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
E-number FI	4740800
Warranty	3 years
Optical data	
Colour temperature (K)	6500

RefLED R50

REFLED R50 V3 470LM 865 E14 SL

0026335

Light colour	Daylight
Colour Variation Initial (SDCM)	SDCM6
Colour Consistency (SDCM)	6
Luminous Intensity (cd)	136
Beam Angle (°)	120

Electrical data

Starting time (max) (s)	0.5
Mains voltage (V)	220-240V
Product Voltage (V)	230
Lamp power factor	0.5
Dimmable	No
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	83
Nominal Product Diameter (mm)	50
Weight (kg)	0.024

Packaging

Single packaging type	Carton
Product EAN number	5410288263359
Packaging single length / height (cm)	5.0
Packaging single width (cm)	5.0
Packaging single depth (cm)	7.8
Units per outer package	6
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	8.8

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures