

ToLEDo Striplight
ToLEDo Striplight V3 300MM 450LM S14s
0028105



- Product features**
- LED Striplight replacement for incandescent lamp
 - High lumen output: up to 806lm
 - 15,000 hours average rated life
 - Up to 85% energy saving
 - Creates a warm ambiance similar to traditional lamps
 - Perfect for kitchen, mirror lighting, shaver lighting, bathroom
 - 3 year warranty



PRODUCT OVERVIEW

Product name	ToLEDo Striplight V3 300MM 450LM S14s
Technology	LED

ToLEDo Striplight

ToLEDo Striplight V3 300MM 450LM S14s

0028105

Watt (Rated) (W)	5
Type	LED exchangeable
Cap/Base	S14s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
E-number FI	4741150
Warranty	3 years
Luminous flux (lm)	450
Colour temperature (K)	2700
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288281056

DATA TABLE

General data

Product name	ToLEDo Striplight V3 300MM 450LM S14s
Technology	LED
Watt (Rated) (W)	5
Type	LED exchangeable
Cap/Base	S14s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4741150
Warranty	3 years

Optical data

Luminous flux (lm)	450
Luminous flux (Rated) (lm)	450
Colour temperature (K)	2700
Correlated colour temperature range (K)	2430 - 2970
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Equivalent watt (W)	35
Starting time (max) (s)	0.5
Product Voltage (V)	230
Lamp power factor	1

ToLEDo Striplight

ToLEDo Striplight V3 300MM 450LM S14s

0028105

Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	2.4
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	460
Max. Luminaires per 13A C Breaker	598
Max. Luminaires per 16A B Breaker	33

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	298
Nominal Product Diameter (mm)	48
Weight (kg)	0.08

Packaging

Single packaging type	Carton
Product EAN number	5410288281056
Packaging single length / height (cm)	30.7
Packaging single width (cm)	5.0
Packaging single depth (cm)	3.0
Units per outer package	6
Packaging outer width (cm)	10.6
Packaging outer depth (cm)	10.1


Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures


PHOTOMETRY

ToLEDo Striplight

ToLEDo Striplight V3 300MM 450LM S14s
0028105



TECHNICAL DRAWINGS




ToLEDo Striplight
ToLEDo Striplight V3 300MM 450LM S14s
0028105

**ENERG**

SYLVANIA

0028105



5

kWh/1000h




2019/2015

ToLEDo Striplight
ToLEDo Striplight V3 300MM 450LM S14s
0028105



0028105



5
kWh/1000h

