

TOLEDO BALL

ToLEDo BALL V6 806LM 840 E27 SL

0028436



Product features

- Compact and elegant design• Suitable replacement for halogen, incandescent and compact fluorescent ball lamps• Instant light at the flick of a switch• Uniform light distribution• Good colour rendering (CRI 80)• Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas• Lower maintenance costs• A+ energy rating



PRODUCT OVERVIEW

Product name	ToLEDo BALL V6 806LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
E-number FI	4740809
Warranty	3 years
Luminous flux (lm)	806
Colour temperature (K)	4000
Light colour	Cool White
Beam Angle (°)	150
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288284361

DATA TABLE

General data

Product name	ToLEDo BALL V6 806LM 840 E27 SL
Technology	LED
Watt (Rated) (W)	8
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
E-number FI	4740809
Warranty	3 years

Optical data

Luminous flux (lm)	806
Luminous flux (Rated) (lm)	806
Colour temperature (K)	4000

TOLEDO BALL

ToLEDo BALL V6 806LM 840 E27 SL

0028436

Light colour	Cool White
Beam Angle (°)	150
Lumen maintenance at end of nominal life (%)	70

Electrical data

Equivalent watt (W)	60
Starting time (max) (s)	0.5
Product Voltage (V)	230
Lamp power factor	0.5
Inrush Current (A)	2.7
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	131

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	90
Nominal Product Diameter (mm)	45
Weight (kg)	0.045

Packaging

Single packaging type	Carton
Product EAN number	5410288284361
Packaging single length / height (cm)	4.5
Packaging single width (cm)	4.5
Packaging single depth (cm)	8.9
Units per outer package	6
Packaging outer width (cm)	9.7
Packaging outer depth (cm)	8.5

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures