



Product features

- LED Striplight replacement for incandescent lamp
- High lumen output: up to 806lm
- 15,000 hours average rated life
- Up to 85% energy saving
- Creates a warm ambiance similar to traditional lamps
- Perfect for kitchen, mirror lighting, shaver lighting, bathroom
- 3 year warranty











PRODUCT OVERVIEW

Product name	ToLEDo Striplight V3 500MM 700LM S14s
Technology	LED
Watt (Rated) (W)	7.5
Туре	LED exchangeable
Cap/Base	S14s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
E-number FI	4741151
Warranty	3 years
Luminous flux (Im)	700
Colour temperature (K)	2700
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288281063



DATA TABLE

General data	
Product name	ToLEDo Striplight V3 500MM 700LM S14s
Technology	LED
Watt (Rated) (W)	7.5
Туре	LED exchangeable
Cap/Base	S14s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4741151
Warranty	3 years
	.,
Optical data	
Luminous flux (lm)	700
Luminous flux (Rated) (Im)	700
Colour temperature (K)	2700
Correlated colour temperature range (K)	2430 - 2970
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal	70
life (%)	
Electrical data	
Equivalent watt (W)	50
Starting time (max) (s)	0.5
Product Voltage (V)	230
Lamp power factor	1
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	2.8
Lamp Energy Label (class)	F
kWh per 1000 hours burning time	8
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	287
Max. Luminaires per 13A C Breaker	373
Max. Luminaires per 16A B Breaker	29
Lifetime data	
Lifespan L70 B50	15000
Average life (Nominal) (h)	
Average me avoningi) (II)	15000
Average life (Rated) (h)	15000 15000



Physical data

Nominal Product Length (mm)	498
Nominal Product Diameter (mm)	48
Weight (kg)	0.116


Packaging

Single packaging type	Carton
Product EAN number	5410288281063
Packaging single length / height (cm)	50.4
Packaging single width (cm)	5.0
Packaging single depth (cm)	3.0
Units per outer package	6
Packaging outer width (cm)	10.6
Packaging outer depth (cm)	10.1

Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS





