

ToLEDo NEOS T8 CCG and AC
TOLEDO T8 2FT 800lm 840 20K
0028230



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps. Omnidirectional 320° uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes. High lumen efficacy - 100 lm/W. Energy rating - A+. Switching cycles - 100,000X. Average rated life 20,000 hours lifespan (L70 F50). Wide beam angle - 220°. High power factor - 0.50. Suitable for general illumination in offices, supermarkets, department stores, parking lots. Suitable for operation with electromagnetic gears and direct mains operation (220-240V). 2-Year warranty.



PRODUCT OVERVIEW

Product name	TOLEDO T8 2FT 800lm 840 20K
Technology	LED
Watt (Rated) (W)	8
Cap/Base	G13
General application	Logistics & Industry, Education, Residential & Consumer, Office
E-number FI	4940752
Warranty	2 years
Luminous flux (lm)	800
Colour temperature (K)	4000
Light colour	Cool White
Product Voltage (V)	230
Average life (Nominal) (h)	20000
Product EAN number	5410288282305

DATA TABLE

General data

Product name	TOLEDO T8 2FT 800lm 840 20K
Technology	LED
Watt (Rated) (W)	8
Cap/Base	G13
General application	Logistics & Industry, Education, Residential & Consumer, Office
E-number FI	4940752
Warranty	2 years

Optical data

Luminous flux (lm)	800
Luminous flux (Rated) (lm)	800
Colour temperature (K)	4000
Light colour	Cool White
Lumen maintenance at end of nominal life (%)	70

Electrical data

ToLEDo NEOS T8 CCG and AC

TOLEDO T8 2FT 800lm 840 20K

0028230

Equivalent watt (W)	18
Starting time (max) (s)	0.5
Product Voltage (V)	230
Lamp power factor	0.55
Inrush Current (A)	2.8
Max. Luminaires per 10A C Breaker	287

Lifetime data

Average life (Nominal) (h)	20000
Average life (Rated) (h)	20000

Physical data

Nominal Product Length (mm)	603
Nominal Product Diameter (mm)	28
Max. Length base to base (mm) - A	589
Weight (kg)	0.105

Packaging

Single packaging type	Carton
Product EAN number	5410288282305
Packaging single length / height (cm)	64.5
Packaging single width (cm)	2.75
Packaging single depth (cm)	2.75
Units per outer package	10
Packaging outer width (cm)	22.6
Packaging outer depth (cm)	11.7

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Safety message	Not Suitable for totally enclosed fixtures