

ToLEDo NEOS T8 CCG and AC

TOLEDO T8 5FT 2000LM 840 20K **0028236**

Product features

Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps.
 Omnidirectional 320° uniform light distribution thanks to glass tube construction design, same as
 traditional fluorescent T8 tubes. High lumen efficacy - 100 lm/W. Energy rating - A+. Switching cycles 100,000X. Average rated life 20,000 hours lifespan (L70 F50). Wide beam angle - 220°. High power
 factor - 0.50. Suitable for general illumination in offices, supermarkets, department stores, parking lots.
 Suitable for operation with electromagnetic gears and direct mains operation (220-240V). 2-Year
 warranty.



PRODUCT OVERVIEW

Product name	TOLEDO T8 5FT 2000LM 840 20K
Technology	LED
Watt (Rated) (W)	20
Cap/Base	G13
General application	Logistics & Industry, Education, Residential & Consumer, Office
E-number FI	4940760
Warranty	2 years
Luminous flux (Im)	2000
Colour temperature (K)	4000
Light colour	Cool White
Product Voltage (V)	230
Average life (Nominal) (h)	20000
Product EAN number	5410288282367

DATA TABLE

General data	
Product name	TOLEDO T8 5FT 2000LM 840 20K
Technology	LED
Watt (Rated) (W)	20
Cap/Base	G13
General application	Logistics & Industry, Education, Residential & Consumer, Office
E-number FI	4940760
Warranty	2 years
Optical data	
Luminous flux (Im)	2000
Luminous flux (Rated) (Im)	2000
Colour temperature (K)	4000
Light colour	Cool White
Lumen maintenance at end of nominal life (%)	70
Electrical data	



ToLEDo NEOS T8 CCG and AC

TOLEDO T8 5FT 2000LM 840 20K **0028236**

Equivalent watt (W)	58
Starting time (max) (s)	0.5
Product Voltage (V)	230
Lamp power factor	0.55
Inrush Current (A)	4
Max. Luminaires per 10A C Breaker	115
Lifetime data	
Average life (Nominal) (h)	20000
Average life (Rated) (h)	20000
Physical data	
Nominal Product Length (mm)	1513
Nominal Product Diameter (mm)	28
Max. Length base to base (mm) - A	1499
Weight (kg)	0.264
Packaging	
Single packaging type	Carton
Product EAN number	5410288282367
Packaging single length / height (cm)	
	155.5
Packaging single width (cm)	155.5 2.75
Packaging single width (cm)	2.75
Packaging single width (cm) Packaging single depth (cm)	2.75 2.75
Packaging single width (cm) Packaging single depth (cm) Units per outer package	2.75 2.75 10
Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm)	2.75 2.75 10 22.6
Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm) Packaging outer depth (cm)	2.75 2.75 10 22.6
Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm) Packaging outer depth (cm) Safety data	2.75 2.75 10 22.6 11.7
Packaging single width (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm) Packaging outer depth (cm) Safety data Breakage cleaning instructions	2.75 2.75 10 22.6 11.7