

ToLEDo AVANT T8 CCG and AC
TOLEDO T8 V4 2FT 10W 1000LM 830 RL
0028800



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps. Omnidirectional 320° uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes. High lumen package - 1000 lm/W. High lumen efficacy - 100 lm/W. Energy rating - A+. Switching cycles - 200,000X. Average life 40,000 hours lifespan (L70 F50). Wide beam angle - 220°. High power factor - 0.90. Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications. Suitable for operation with electromagnetic gears and direct mains operation (220-240V). 3-Year warranty.



PRODUCT OVERVIEW

Product name	TOLEDO T8 V4 2FT 10W 1000LM 830 RL
Technology	LED
Watt (Rated) (W)	10
Lamp finish	Frosted/Coated
General application	Logistics & Industry, Education, Residential & Consumer, Office, Hospitality, Retail, Museums & Galleries
Warranty	3 years
Luminous flux (lm)	1000
Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
Colour Consistency (SDCM)	6
Product Voltage (V)	4
Dimmable	No
Average life (Nominal) (h)	40000
IP rating	IP20
Product EAN number	5410288288000

DATA TABLE

General data	
Product name	TOLEDO T8 V4 2FT 10W 1000LM 830 RL
Technology	LED
Watt (Rated) (W)	10
Lamp finish	Frosted/Coated
General application	Logistics & Industry, Education, Residential & Consumer, Office, Hospitality, Retail, Museums & Galleries
Performance ambient temperature Tq (°C)	25
Warranty	3 years
Optical data	
Luminous flux (lm)	1000
Luminous flux (Rated) (lm)	1000

ToLEDo AVANT T8 CCG and AC

TOLEDO T8 V4 2FT 10W 1000LM 830 RL
0028800

Colour temperature (K)	3000
Light colour	Warm White
Colour Code	830
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	70

Electrical data

Starting time (max) (s)	0.5
Current (A)	0.045
Mains voltage (V)	230V
Product Voltage (V)	4
Lamp power factor	0.9
Control gear required	No
Transformer required	No
Dimmable	No
kWh per 1000 hours burning time	10

Lifetime data

Average life (Nominal) (h)	40000
Average life (Rated) (h)	40000

Physical data

IP rating	IP20
Nominal Product Length (mm)	603
Max. Length base to base (mm) - A	589
Length base to pin Min-Max (mm) - B	596
Max. Lamp Length (mm) - C/L	603
Max. Lamp Diameter (mm) - D	28
Weight (kg)	0.125

Packaging

Single packaging type	Carton
Product EAN number	5410288288000
Packaging single length / height (cm)	68.7
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
Units per outer package	10
Packaging outer width (cm)	22.0
Packaging outer depth (cm)	10.0

Safety data

Breakage cleaning instructions	Not applicable
Recommendation for disposal at end of life	Not Applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for accent lighting	Yes



ToLEDo AVANT T8 CCG and AC

TOLEDO T8 V4 2FT 10W 1000LM 830 RL
0028800

Safety message

Suitable for totally enclosed fixture