

RefLED PAR30

RefLED Retro PAR30 V2 DIM 820L 840 36 SL

0029199



Product features

- High performance LED PAR30 lamp with the same look and feel of traditional PAR lamps
- Glass construction - means no colours clashing between the lamp and fixture
- Reduced visible heatsink from the front
- Mercury-free solution
- Lower maintenance cost
- Lifetime: up to 25,000 hours
- High lumen efficacy
- Dimmable with approved dimmers*
- 3 year warranty
- Suitable for general lighting and accent lighting for hotels, restaurants, bars, lobbies, corridors and halls



PRODUCT OVERVIEW

Product name	RefLED Retro PAR30 V2 DIM 820L 840 36 SL
Technology	LED
Watt (Rated) (W)	11
Type	LED exchangeable
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
E-number FI	4741081
Warranty	3 years
Colour temperature (K)	4000
Light colour	Cool White
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	36
Photobiological Risk Group	RG1
Product Voltage (V)	230
Dimmable	Yes
Average life (Nominal) (h)	25000
Product EAN number	5410288291994

DATA TABLE

General data

Product name	RefLED Retro PAR30 V2 DIM 820L 840 36 SL
Technology	LED
Watt (Rated) (W)	11
Type	LED exchangeable
Fixture rating	Open
General application	Hospitality, Museums & Galleries, Residential & Consumer, Retail
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25

RefLED PAR30

RefLED Retro PAR30 V2 DIM 820L 840 36 SL

0029199

E-number FI	4741081
Warranty	3 years

Optical data

Colour temperature (K)	4000
Light colour	Cool White
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	SDCM6
Luminous Intensity (cd)	1900
Beam Angle (°)	36
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

Electrical data

Equivalent watt (W)	95
Product Voltage (V)	230
Control gear required	No
Transformer required	No
Dimmable	Yes
Inrush Current (A)	2.2
Lamp Energy Label (class)	F

Lifetime data

Lifespan L70 B50	25000
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

Nominal Product Length (mm)	94
Nominal Product Diameter (mm)	95
Weight (kg)	0.234

Packaging

Single packaging type	Carton
Product EAN number	5410288291994
Packaging single length / height (cm)	10.3
Packaging single width (cm)	10.3
Packaging single depth (cm)	11.1
Units per outer package	6
Packaging outer width (cm)	24.1
Packaging outer depth (cm)	15.5

Safety data


Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Dimmable with approved dimmers

RefLED PAR30


RefLED Retro PAR30 V2 DIM 820L 840 36 SL

0029199

PHOTOMETRY



TECHNICAL DRAWINGS



RefLED PAR30

RefLED Retro PAR30 V2 DIM 820L 840 36 SL

0029199



SYLVANIA

0029199



11
kWh/1000h



2019/2015

RefLED PAR30
RefLED Retro PAR30 V2 DIM 820L 840 36 SL
0029199



0029199



11
kWh/1000h



2019/2015