

RefLED R39

RefLED R39 V4 250LM 830 E14 SL

0029202



Product features

- Energy efficient LED alternative for traditional incandescent and halogen blown reflector lamp
- Modern construction and attractive design
- Mercury free solution
- Long average rated lifetime: 15,000 hours
- Lower maintenance cost compared to traditional lamps
- Non-dimmable
- 3 years warranty
- Perfect for general lighting applications: residential lighting, down lights, hotels, hotels, restaurants, bars, lobbies, corridors, halls, etc



PRODUCT OVERVIEW

Product name	RefLED R39 V4 250LM 830 E14 SL
Technology	LED
Watt (Rated) (W)	2.9
Type	LED exchangeable
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
E-number FI	4741084
Warranty	3 years
Luminous flux (lm)	250
Colour temperature (K)	3000
Light colour	Warm White
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Photobiological Risk Group	RG1
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288292021

DATA TABLE

General data

Product name	RefLED R39 V4 250LM 830 E14 SL
Technology	LED
Watt (Rated) (W)	2.9
Type	LED exchangeable

RefLED R39

RefLED R39 V4 250LM 830 E14 SL

0029202

Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4741084
Warranty	3 years

Optical data

Luminous flux (lm)	250
Colour temperature (K)	3000
Light colour	Warm White
Colour Consistency (SDCM)	6
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

Electrical data

Equivalent watt (W)	25
Product Voltage (V)	230
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	1.2
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A B Breaker	67

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	67
Nominal Product Diameter (mm)	39
Weight (kg)	0.055

Packaging


Single packaging type	Carton
Product EAN number	5410288292021
Packaging single length / height (cm)	8.35
Packaging single width (cm)	5.0
Packaging single depth (cm)	5.0
Units per outer package	6
Packaging outer width (cm)	10.7

RefLED R39
RefLED R39 V4 250LM 830 E14 SL
0029202


Packaging outer depth (cm) 9.1

Safety data	
Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS



RefLED R39
RefLED R39 V4 250LM 830 E14 SL
0029202

**ENERG**

SYLVANIA

0029202



3

kWh/1000h




2019/2015

RefLED R39
RefLED R39 V4 250LM 830 E14 SL
0029202



0029202



3
kWh/1000h

