



Product features

- Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps
- The versatile ToLEDo Retro ball range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications
- · Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- Gives same sparkling light effect as the incandescent lamp
- Dimensionally identical to incandescent lamps fits all fixtures
- Environment-friendly no mercury and lower CO2 emissions



PRODUCT OVERVIEW

Product name	ToLEDo RT Ball CL 470LM 827 E27 SL4
Technology	LED
Watt (Rated) (W)	4.5
Туре	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
Warranty	2 years
Luminous flux (Im)	470
Colour temperature (K)	2700
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288295527

DATA TABLE

General	l data

Product name	ToLEDo RT Ball CL 470LM 827 E27 SL4
Technology	LED
Watt (Rated) (W)	4.5
Туре	LED exchangeable
Cap/Base	E27
Fixture rating	Open



General application	Residential & Consumer
	0000 4000
Operating temperature range (°C)	-20°C+40°C
Performance ambient temperature Tq (°C)	25
Warranty	2 years
Optical data	
Luminous flux (Im)	470
Luminous flux (IIII) Luminous flux (Rated) (Im)	470
	2700
Colour temperature (K)	
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Equivalent watt (W)	40
Product Voltage (V)	230
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	6.3
` '	
Lamp Energy Label (class)	F
Lamp Energy Label (class)	F 50/60H 7
Nominal Frequency (Hz)	50/60Hz
	•
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker	50/60Hz
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data	50/60Hz
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50	50/60Hz 13
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h)	50/60Hz 13
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h)	50/60Hz 13 12000 15000
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h)	50/60Hz 13 12000 15000
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h)	50/60Hz 13 12000 15000
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data	50/60Hz 13 12000 15000 15000
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm)	50/60Hz 13 12000 15000 15000
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm)	50/60Hz 13 12000 15000 15000 78 45
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging	50/60Hz 13 12000 15000 15000 78 45
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type	50/60Hz 13 12000 15000 15000 78 45 0.18
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number	50/60Hz 13 12000 15000 15000 78 45 0.18 Carton 5410288295527
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm)	50/60Hz 13 12000 15000 15000 78 45 0.18 Carton 5410288295527 9.5
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm)	50/60Hz 13 12000 15000 15000 78 45 0.18 Carton 5410288295527 9.5 19.7
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	50/60Hz 13 12000 15000 15000 78 45 0.18 Carton 5410288295527 9.5 19.7 5.0
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Units per outer package	50/60Hz 13 12000 15000 15000 78 45 0.18 Carton 5410288295527 9.5 19.7 5.0 6
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single width (cm) Packaging single depth (cm)	50/60Hz 13 12000 15000 15000 78 45 0.18 Carton 5410288295527 9.5 19.7 5.0
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm) Packaging outer depth (cm)	50/60Hz 13 12000 15000 15000 78 45 0.18 Carton 5410288295527 9.5 19.7 5.0 6 31.1
Nominal Frequency (Hz) Max. Luminaires per 16A B Breaker Lifetime data Lifespan L70 B50 Average life (Nominal) (h) Average life (Rated) (h) Physical data Nominal Product Length (mm) Nominal Product Diameter (mm) Weight (kg) Packaging Single packaging type Product EAN number Packaging single length / height (cm) Packaging single depth (cm) Units per outer package Packaging outer width (cm)	50/60Hz 13 12000 15000 15000 78 45 0.18 Carton 5410288295527 9.5 19.7 5.0 6 31.1




Breakage cleaning instructions Not applicable

Special purpose lamp No
Dry applications use only Yes

Safety message Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS

