

ToLEDo Superia T8 CCG and AC
ToLEDo SUPERIA T8 CCG L 1500 4100LM 865 75K PET SL
0030250



Product features

- A range of high performance ToLEDo Superia T8 LED tubes with reminiscent look of fluorescent tubesHigh performance glass construction designHigh lumen output, with an impressive lumen efficacy of 185 lm/WOmnidirectional light distribution and wide beam angle Average rated life of 75,000 hoursLamp length - 1500mmHigh power factor200,000 switching cycle5 years warranty for complete peace of mindCompatible with electromagnetic gear / CCG and also suitable for direct mains operation (220-240V)No bending or discoloration over timeSuitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots, waterproof luminaires and maintenance free applications



PRODUCT OVERVIEW

Product name	ToLEDo SUPERIA T8 CCG L 1500 4100LM 865 75K PET SL
Technology	LED
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer
E-number FI	4941355
Warranty	5 years
Colour temperature (K)	6500
Light colour	Daylight
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	170
Photobiological Risk Group	RG0
Product Voltage (V)	230
Dimmable	No
IP rating	IP20
Product EAN number	5410288302508

DATA TABLE

General data	
Product name	ToLEDo SUPERIA T8 CCG L 1500 4100LM 865 75K PET SL
Technology	LED
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Frosted/Coated
General application	Hospitality, Logistics & Industry, Residential & Consumer
Operating temperature range (°C)	-20°C...+55°C
E-number FI	4941355
Warranty	5 years
Optical data	
Colour temperature (K)	6500

ToLEDo Superia T8 CCG and AC

ToLEDo SUPERIA T8 CCG L 1500 4100LM 865 75K PET SL
0030250

Light colour	Daylight
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	170
Photobiological Risk Group	RG0

Electrical data

Product Voltage (V)	230
Lamp power factor	0.9
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	16.2
Lamp Energy Label (class)	C

Lifetime data

Lifespan L70 B50	75000
------------------	-------

Physical data

IP rating	IP20
Nominal Product Length (mm)	1499
Nominal Product Diameter (mm)	28
Weight (kg)	0.26

Packaging


Single packaging type	Carton
Product EAN number	5410288302508
Packaging single length / height (cm)	155.5
Packaging single width (cm)	2.9
Packaging single depth (cm)	2.9
Units per outer package	10
Packaging outer width (cm)	22.0
Packaging outer depth (cm)	10.5

Safety data


Optimal operating condition (°C)	-20-55
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Safety message	Suitable for totally enclosed fixture

PHOTOMETRY

ToLEDo Superia T8 CCG and AC
ToLEDo SUPERIA T8 CCG L 1500 4100LM 865 75K PET SL
0030250




TECHNICAL DRAWINGS



ToLEDo Superia T8 CCG and AC
ToLEDo SUPERIA T8 CCG L 1500 4100LM 865 75K PET SL
0030250


SYLVANIA
0030250




23
kWh/1000h



ToLEDo Superia T8 CCG and AC
ToLEDo SUPERIA T8 CCG L 1500 4100LM 865 75K PET SL
0030250

**ENERG**
SYLVANIA
0030250



23
kWh/1000h

