

START DOWNLIGHT IP44 225
START Downlight 225 IP44 2325lm 840
0030331



Product features

- Ceiling recessed LED downlight IP44 (from the front), perfect where limited ceiling void is available with only 65mm product depth and 225mm cutout. Ideal replacement for 2x26W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Loop in loop out connector allows for quick installation. Die-cast aluminium body, 2325LM, 23W, 101lm/W, 4000K, Driver Current: 630mA, CRI80, 74° beam angle, Non-dimmable LED driver, IP44 from the front, IK07, (HxW) 65x225mm, Class 2, 220-240V. Meets TP(a) requirements.



PRODUCT OVERVIEW

Product name	START Downlight 225 IP44 2325lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Logistics & Industry, Office
E-number FI	4278156
Warranty	5 years
Fixture luminous flux (lm)	2325
Luminous flux (lm)	2325
Luminaire efficacy (lm/W)	101
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	74
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	23
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303314

DATA TABLE

START DOWNLIGHT IP44 225

START Downlight 225 IP44 2325lm 840

0030331

General data

Product name	START Downlight 225 IP44 2325lm 840
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Logistics & Industry, Office
Operating temperature range (°C)	-10°C...+40°C
Performance ambient temperature T _a (°C)	40
E-number FI	4278156
Warranty	5 years

Optical data

Fixture luminous flux (lm)	2325
Luminous flux (lm)	2325
Luminaire efficacy (lm/W)	101
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM3
Adjustable chromaticity	N
Beam Angle (°)	74
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	23
Mains voltage (V)	220-240V
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	No
Dimming method	N/A
Inrush Current (A)	6.44
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	20
Max. Luminaires per 13A C Breaker	26
Max. Luminaires per 10A B Breaker	12
Max. Luminaires per 16A B Breaker	19
Max. Luminaires per 20A B Breaker	24

START DOWNLIGHT IP44 225

START Downlight 225 IP44 2325lm 840
0030331

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	74000
Lifespan L90 B10	34000

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Reflector finish	High-gloss
Nominal Product Diameter (mm)	240
Cutout Dimensions (W x L in mm or Diameter in mm)	225
Weight (kg)	0.528
Recessed Depth (mm)	150



Packaging

Single packaging type	Carton
Product EAN number	5410288303314
Packaging single length / height (cm)	24.5
Packaging single width (cm)	24.5
Packaging single depth (cm)	8.0
Units per outer package	12
Packaging outer width (cm)	51.0
Packaging outer depth (cm)	27.0

Safety data

Optimal operating condition (°C)	-10-40
----------------------------------	--------

PHOTOMETRY



START DOWNLIGHT IP44 225

START Downlight 225 IP44 2325lm 840
0030331

TECHNICAL DRAWINGS

