

ToLEDo GLS

ToLEDo GLS 1521LM 827 E27 SL4

0029641



Product features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- 12,000 hours average rated life



PRODUCT OVERVIEW

Product name	ToLEDo GLS 1521LM 827 E27 SL4
Technology	LED
Watt (Rated) (W)	13
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
Warranty	2 years
Luminous flux (lm)	1521
Colour temperature (K)	2700
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288296418

DATA TABLE

General data

Product name	ToLEDo GLS 1521LM 827 E27 SL4
Technology	LED
Watt (Rated) (W)	13

ToLEDo GLS

ToLEDo GLS 1521LM 827 E27 SL4

0029641

Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
Warranty	2 years

Optical data

Luminous flux (lm)	1521
Luminous flux (Rated) (lm)	1521
Colour temperature (K)	2700
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Equivalent watt (W)	100
Product Voltage (V)	230
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	6
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A B Breaker	13

Lifetime data

Lifespan L70 B50	12000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	120
Nominal Product Diameter (mm)	60
Weight (kg)	0.31

Packaging


Single packaging type	Carton
Product EAN number	5410288296418
Packaging single length / height (cm)	12.3
Packaging single width (cm)	6.1
Packaging single depth (cm)	21.0
Units per outer package	6
Packaging outer width (cm)	37.7
Packaging outer depth (cm)	21.6

ToLEDo GLS
ToLEDo GLS 1521LM 827 E27 SL4
0029641


Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS



ToLEDo GLS
ToLEDo GLS 1521LM 827 E27 SL4
0029641

**ENERG**

SYLVANIA

0029641



13
kWh/1000h



ToLEDo GLS
ToLEDo GLS 1521LM 827 E27 SL4
0029641



0029641



13
kWh/1000h



2019/2015