



Product features

- ToLEDo R7s is a retrofit replacement for traditional halogen double-ended linear R7s lamps
- The slim design and glass construction give the same look and feel of traditional halogen R7s lamp
- Omni-directional light distribution
- High lumen efficacy
- Lumen output: 850lm
- 85% energy saving Length: 118mm
- Non-Dimmable
- 15,000 hours average rated life
- Ideal for domestic and commercial applications



PRODUCT OVERVIEW

Product name	ToLEDo Retro R7s 118MM 850LM 827 SL
Technology	LED
Watt (Rated) (W)	7.7
Туре	LED exchangeable
Cap/Base	R7s
Fixture rating	Open



General application	Hospitality, Residential & Consumer
E-number FI	4741121
Warranty	3 years
Luminous flux (Im)	850
Colour temperature (K)	2700
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	15000
Product EAN number	5410288296845

DATA

TA TABLE	
General data	
Product name	ToLEDo Retro R7s 118MM 850LM 827 SL
Technology	LED
Watt (Rated) (W)	7.7
Туре	LED exchangeable
Cap/Base	R7s
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C+45°C
Performance ambient temperature Tq (°C)	25
E-number FI	4741121
Warranty	3 years
Optical data	
Luminous flux (Im)	850
Luminous flux (Rated) (Im)	850
Colour temperature (K)	2700
Light colour	Homelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Equivalent watt (W)	60
Product Voltage (V)	230
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	1.2
Lamp Energy Label (class)	E
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A B Breaker	66




Lifetime data	
Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
Physical data	
Nominal Product Length (mm)	118
Nominal Product Diameter (mm)	17
Weight (kg)	0.013
Packaging	
Single packaging type	Carton
Product EAN number	5410288296845
Packaging single length / height (cm)	12.0
Packaging single width (cm)	4.5
Packaging single depth (cm)	4.5
Units per outer package	6
Packaging outer width (cm)	9.7
Packaging outer depth (cm)	13.0
Safety data	
Optimal operating condition (°C)	-20-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes

Not Suitable for totally enclosed fixtures

PHOTOMETRY

Safety message



TECHNICAL DRAWINGS



