

TOLEDO CANDLE
ToLEDo Candle V7 250LM 865 E14 SL
0029605



- Product features**
- Compact and elegant design
 - Suitable replacement for halogen, incandescent and compact fluorescent candle lamps
 - Instant light at the flick of a switch
 - Uniform light distribution
 - Good colour rendering (CRI 80)
 - Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
 - Lower maintenance costs
 - 15,000 hours average rated life



PRODUCT OVERVIEW

Product name	ToLEDo Candle V7 250LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	LED exchangeable
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
E-number FI	4740996
Warranty	3 years
Luminous flux (lm)	250
Colour temperature (K)	6500
Light colour	Daylight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Product Voltage (V)	230
Dimmable	No

TOLEDO CANDLE

ToLEDo Candle V7 250LM 865 E14 SL

0029605

Average life (Nominal) (h)	15000
Product EAN number	5410288296050

DATA TABLE

General data

Product name	ToLEDo Candle V7 250LM 865 E14 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	LED exchangeable
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature T _q (°C)	25
E-number FI	4740996
Warranty	3 years

Optical data

Luminous flux (lm)	250
Luminous flux (Rated) (lm)	250
Colour temperature (K)	6500
Light colour	Daylight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Equivalent watt (W)	25
Product Voltage (V)	230
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	1.5
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A B Breaker	53

Lifetime data

Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	104
Nominal Product Diameter (mm)	35
Weight (kg)	0.028

TOLEDO CANDLE

ToLEDo Candle V7 250LM 865 E14 SL

0029605


Packaging

Single packaging type	Carton
Product EAN number	5410288296050
Packaging single length / height (cm)	11.0
Packaging single width (cm)	4.5
Packaging single depth (cm)	4.5
Units per outer package	6
Packaging outer width (cm)	9.7
Packaging outer depth (cm)	11.7


Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS




TOLEDO CANDLE
ToLEDo Candle V7 250LM 865 E14 SL
0029605

**ENERG**

SYLVANIA

0029605



3
kWh/1000h




2019/2015

TOLEDO CANDLE
ToLEDo Candle V7 250LM 865 E14 SL
0029605



0029605



3
kWh/1000h



2019/2015