

Toledo Mirage G200

ToLEDo Mirage G200 105LM E27 SL

0029911



Product features

- A perfect choice for hospitality, decorative and mood lighting applications
- Unique and innovative lamp design and construction
- Low-lumen output to create the low-lit effect and gives no glare
- Low power construction: only 2.5W
- Perfect for SylPendant fixtures - a range of unique and elegant E27 lamp pendants, available in copper, brass, black and white finish
- Candlelight 2000K colour temperature creates a warm and cosy ambience
- High colour rendering - CRI80
- High quality, scratch and temperature resistant golden tinted glass envelope
- 25,000 hours of average rated life. Last 25 times longer than incandescent lamps
- Omni-directional light distribution
- Non-dimmable
- More than 100,000X switching cycles
- 3 years warranty



PRODUCT OVERVIEW

Product name	ToLEDo Mirage G200 105LM E27 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open
General application	Residential & Consumer
E-number FI	4740679
Warranty	3 years
Luminous flux (lm)	105
Colour temperature (K)	2000
Light colour	Candlelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	25000
Product EAN number	5410288299112

DATA TABLE

General data

Product name	ToLEDo Mirage G200 105LM E27 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	LED exchangeable
Cap/Base	E27
Fixture rating	Open

Toledo Mirage G200

ToLEDo Mirage G200 105LM E27 SL

0029911

General application	Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4740679
Warranty	3 years

Optical data

Luminous flux (lm)	105
Luminous flux (Rated) (lm)	105
Colour temperature (K)	2000
Light colour	Candlelight
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Equivalent watt (W)	12
Starting time (max) (s)	0.5
Product Voltage (V)	230
Lamp power factor	0.5
Control gear required	No
Transformer required	No
Dimmable	No
Inrush Current (A)	0.2
Lamp Energy Label (class)	G
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Lifespan L70 B50	25000
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

Nominal Product Length (mm)	238
Nominal Product Diameter (mm)	200
Weight (kg)	0.38

Packaging


Single packaging type	Carton
Product EAN number	5410288299112
Packaging single length / height (cm)	26.0
Packaging single width (cm)	21.0
Packaging single depth (cm)	21.0
Units per outer package	2
Packaging outer width (cm)	22.5
Packaging outer depth (cm)	28.5

Toledo Mirage G200
ToLEDo Mirage G200 105LM E27 SL
0029911


Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS




Toledo Mirage G200
ToLEDo Mirage G200 105LM E27 SL
0029911



ENERG

SYLVANIA

0029911




3
kWh/1000h



Toledo Mirage G200
ToLEDo Mirage G200 105LM E27 SL
0029911



0029911



3
kWh/1000h

