

Sylvania Granit DALI - NEW
Granit IP65 DALI 19500lm 840 MB
0039750



Product features

- Integrated LED highbay; Black aluminium housing; 19500lm; 120 W; 163 Lm/W; 4000K; Drive current: 470mA; CRI 80; 55° beam angle; DALI dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 298 x 168 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.



PRODUCT OVERVIEW

Product name	Granit IP65 DALI 19500lm 840 MB
Technology	LED
General application	Logistics & Industry
Warranty	5 years
Fixture luminous flux (lm)	19500
Luminaire efficacy (lm/W)	163
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	55
Glare control	< 22
Photobiological Risk Group	RG1
Total power consumption (W)	120
Electrical protection	Class I
Dimmable	Yes
Dimming method	DALI-2
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288397504

DATA TABLE

General data	
Product name	Granit IP65 DALI 19500lm 840 MB
Technology	LED
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
Warranty	5 years
Optical data	
Fixture luminous flux (lm)	19500

Sylvania Granit DALI - NEW

Granit IP65 DALI 19500lm 840 MB

0039750

Luminaire efficacy (lm/W)	163
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	55
Distribution type	Symmetric
Glare control	< 22
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	120
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	15
Electrical protection	Class I
Dimmable	Yes
Dimming method	DALI-2
Inrush Current (A)	77
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	16
Max. Luminaires per 13A C Breaker	20
Max. Luminaires per 10A B Breaker	10
Max. Luminaires per 16A B Breaker	16
Max. Luminaires per 20A B Breaker	20
Mains surge immunity (differential mode - > L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

Lifetime data

Lifespan L70 B50	90000
Lifespan L70 B20	90000
Lifespan L70 B10	90000
Lifespan L80 B50	90000
Lifespan L80 B20	82000
Lifespan L80 B10	77000
Lifespan L90 B50	44000
Lifespan L90 B20	40000
Lifespan L90 B10	37000

Physical data

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Diameter (mm)	298

Sylvania Granit DALI - NEW
Granit IP65 DALI 19500lm 840 MB
0039750

Weight (kg)	2.243
Packaging	
Single packaging type	Carton
Product EAN number	5410288397504
Packaging single length / height (cm)	32.5
Packaging single width (cm)	32.5
Packaging single depth (cm)	14.5
Units per outer package	1
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	14.5
Safety data	
Optimal operating condition (°C)	-30-50

PHOTOMETRY

