

Sylvania Granit DALI - NEW
Granit IP65 DALI 13000lm 840 WB
0039752



Product features

- Integrated LED highbay; Black aluminium housing; 13000Lm; 80 W; 163 Lm/W; 4000K; Drive current: 410mA; CRI 80; 85° beam angle; DALI dimmable; IP65; IK08; Lifespan L80:B50 90,000 hrs; (D x H) 298 x 168 mm; 1.5 m mains cable; 1.5 m control cable; 1.2 m chain length including hooks.



PRODUCT OVERVIEW

Product name	Granit IP65 DALI 13000lm 840 WB
Technology	LED
General application	Logistics & Industry
E-number FI	4357105
Warranty	5 years
Fixture luminous flux (lm)	13000
Luminaire efficacy (lm/W)	163
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	80
Electrical protection	Class I
Dimmable	Yes
Dimming method	DALI-2
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288397528

DATA TABLE

General data	
Product name	Granit IP65 DALI 13000lm 840 WB
Technology	LED
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
E-number FI	4357105
Warranty	5 years

Sylvania Granit DALI - NEW

Granit IP65 DALI 13000lm 840 WB
0039752

Optical data

Fixture luminous flux (lm)	13000
Luminaire efficacy (lm/W)	163
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	85
Distribution type	Symmetric
Glare control	< 25
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	80
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	15
Electrical protection	Class I
Dimmable	Yes
Dimming method	DALI-2
Inrush Current (A)	77
Glow Wire Test (°C)	850
Energy Efficiency Class (A->G) of contained light source	C
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	16
Max. Luminaires per 13A C Breaker	20
Max. Luminaires per 10A B Breaker	10
Max. Luminaires per 16A B Breaker	16
Max. Luminaires per 20A B Breaker	20
Mains surge immunity (differential mode - > L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	6

Lifetime data

Lifespan L80 B50	90000
Lifespan L80 B20	82000
Lifespan L90 B50	44000

Physical data

Housing colour	RAL 9017 - Traffic black
IP rating	IP65
IK rating	IK08
Nominal Product Diameter (mm)	298
Weight (kg)	2.243

Packaging

Single packaging type	Carton
-----------------------	--------

Sylvania Granit DALI - NEW

Granit IP65 DALI 13000lm 840 WB
0039752

Product EAN number	5410288397528
Packaging single length / height (cm)	32.5
Packaging single width (cm)	32.5
Packaging single depth (cm)	14.5
Units per outer package	1
Packaging outer width (cm)	32.5
Packaging outer depth (cm)	14.5

Safety data

Optimal operating condition (°C)	-30-50
----------------------------------	--------

PHOTOMETRY

