

## SylSafe Monitor

### N-Light Emergency Monitor

0041774



#### Product features

- N-Light Emergency Monitor is a DALI Emergency lighting test and monitoring system. Works with DALI monitoring capable SylSafe products. Controls two DALI subnets with maximum 128 luminaires. For larger systems multiple N-Light monitors can be networked together. Touch screen controlled. Comes with long life CR2032 battery to retain information during power failure. Ethernet port for commissioning and networking. Commissioned with N-Light software. Password protected Engineering Mode. Available in recessed and surface mounting versions. Power consumption: 4.14W



## PRODUCT OVERVIEW

|                       |                                                                                   |
|-----------------------|-----------------------------------------------------------------------------------|
| Product name          | N-Light Emergency Monitor                                                         |
| Technology            | Controls                                                                          |
| Mount                 | Ceiling surface mounting                                                          |
| General application   | Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail |
| Warranty              | 5 years                                                                           |
| Electrical protection | Class I                                                                           |
| IP rating             | IP20                                                                              |
| IK rating             | IK03                                                                              |
| Product EAN number    | 5410288417745                                                                     |

## DATA TABLE

### General data

|                     |                                                                                   |
|---------------------|-----------------------------------------------------------------------------------|
| Product name        | N-Light Emergency Monitor                                                         |
| Technology          | Controls                                                                          |
| Mount               | Ceiling surface mounting                                                          |
| General application | Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail |
| Warranty            | 5 years                                                                           |

### Electrical data

|                       |          |
|-----------------------|----------|
| Mains voltage (V)     | 230-240V |
| Electrical protection | Class I  |

### Physical data

|                               |      |
|-------------------------------|------|
| IP rating                     | IP20 |
| IK rating                     | IK03 |
| Nominal Product Length (mm)   | 4    |
| Nominal Product Width (mm)    | 100  |
| Nominal Product Diameter (mm) | 160  |
| Weight (kg)                   | 0.31 |

### Packaging

|                       |        |
|-----------------------|--------|
| Single packaging type | Carton |
|-----------------------|--------|



SylSafe Monitor  
*N-Light Emergency Monitor*  
0041774

|                                       |               |
|---------------------------------------|---------------|
| Product EAN number                    | 5410288417745 |
| Packaging single length / height (cm) | 30.5          |
| Packaging single width (cm)           | 14.9          |
| Packaging single depth (cm)           | 9.7           |
| Units per outer package               | 9             |
| Packaging outer width (cm)            | 34.8          |
| Packaging outer depth (cm)            | 35.7          |