

SylSafe EXIT Mod  
SylSafe Exit-Mod EX V EM3 MT DA  
0041756



Product features

- SylSafe Exit-Mod EX V EM3 MT DA is a ceiling mounted emergency exit sign. Comes with ISO7010 compliant legend pack. Arrows left, right, up, down and a blank sheet for single sided versions. EC legend pack is available as accessory. Viewing distance 26m. White housing colour. Maintained 3hr emergency operation with NiMH rechargeable battery. Recharge period 24 hours. Self testing with DALI monitoring capability. 4.9W, IK03, IP20. Power Factor 0.49. Class II electrical construction.



PRODUCT OVERVIEW

Product name	SylSafe Exit-Mod EX V EM3 MT DA
Technology	LED
Type	LED
Mount	Ceiling surface mounting
General application	Office, Hospitality, Retail, Museums & Galleries, Education, Logistics & Industry
Warranty	5 years
Fixture luminous flux (lm)	-
Electrical protection	Class II
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288417561

DATA TABLE

General data	
Product name	SylSafe Exit-Mod EX V EM3 MT DA
Technology	LED
Type	LED
Mount	Ceiling surface mounting
General application	Office, Hospitality, Retail, Museums & Galleries, Education, Logistics & Industry
Warranty	5 years
Optical data	
Fixture luminous flux (lm)	-
Emergency duration (h)	3
Electrical data	
Mains voltage (V)	230-240V
Lamp power factor	0.49
Electrical protection	Class II
Control gear required	Yes
Nominal Frequency (Hz)	50/60Hz

SylSafe EXIT Mod  
*SylSafe Exit-Mod EX V EM3 MT DA*  
0041756

Physical data

Housing colour	White
IP rating	IP20
IK rating	IK03
Nominal Product Length (mm)	300
Nominal Product Width (mm)	57
Weight (kg)	0.866

Packaging

Single packaging type	Carton
Product EAN number	5410288417561
Packaging single length / height (cm)	31.0
Packaging single width (cm)	22.6
Packaging single depth (cm)	4.4
Units per outer package	1
Packaging outer width (cm)	22.6
Packaging outer depth (cm)	4.4

TECHNICAL DRAWINGS

