


START Surface IP44 DualTone PIR

START Surface IP44 PIR 1800lm 830/840 DualTone
0043438



Product features

- Ceiling / wall luminaire with integrated LED. Perfect solution for hallways, circulation spaces or foyer. Even and uniform light distribution with a halo lighting effect on the wall surface. Body Size diameter 360mm. Besa mounting box compatible, hole distance 51mm. DualTone functionality enables switch between 3000K and 4000K colour temperatures. Power 24W, output 1800 lumens (4000K). Supplied with integrated PIR (infra-red) sensor for automatic on-off presence control. IK03, IP44. Low maintenance with lifespan 90,000 hours L70:B50.



PRODUCT OVERVIEW

Product name	START Surface IP44 PIR 1800lm 830/840 DualTone
Technology	LED
Cap/Base	N/A
Housing	Steel
Mount	Ceiling surface mounting
General application	Hospitality
E-number FI	4170573
Warranty	3 years
Fixture luminous flux (lm)	1800
Luminaire efficacy (lm/W)	75
Colour temperature (K)	4000
Light colour	Amber White or Neutral White
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	24
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	High (>40%)
Housing colour	White
IP rating	IP44
IK rating	IK03
Product EAN number	5410288434384

DATA TABLE

General data

Product name	START Surface IP44 PIR 1800lm 830/840 DualTone
Technology	LED
Cap/Base	N/A
Housing	Steel

START Surface IP44 DualTone PIR

START Surface IP44 PIR 1800lm 830/840 DualTone
0043438

Mount	Ceiling surface mounting
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4170573
Warranty	3 years

Optical data

Fixture luminous flux (lm)	1800
Luminaire efficacy (lm/W)	75
Colour temperature (K)	4000
Correlated colour temperature range (K)	3000 - 4000
Light colour	Amber White or Neutral White
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Distribution type	Diffuse
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	24
Mains voltage (V)	220-240V
Lamp power factor	0.7
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	70
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Inrush Current (A)	2
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50Hz
LED Flickering Rate	High (>40%)
Max. Luminaires per 10A C Breaker	15
Max. Luminaires per 13A C Breaker	20
Max. Luminaires per 10A B Breaker	9
Max. Luminaires per 16A B Breaker	14
Max. Luminaires per 20A B Breaker	18

Lifetime data

Lifespan L70 B50	90000
Lifespan L80 B50	90000
Lifespan L90 B50	43000

Physical data

Housing colour	White
IP rating	IP44
IK rating	IK03

START Surface IP44 DualTone PIR

START Surface IP44 PIR 1800lm 830/840 DualTone
0043438

Diffuser finish	Opal
Diffuser material	Polypropylene
Nominal Product Diameter (mm)	360
Weight (kg)	0.61





Packaging

Single packaging type	Carton
Product EAN number	5410288434384
Packaging single length / height (cm)	39.0
Packaging single width (cm)	11.8
Packaging single depth (cm)	39.0
Units per outer package	6
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	40.5

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

START Surface IP44 DualTone PIR

START Surface IP44 PIR 1800lm 830/840 DualTone

0043438

