

Emergency KITs

EMERGENCY PACK MANUAL TESTING 6V-55V

0046600

Product features

- The standard, non- Auto test emergency kit enables conversion of general lighting for emergency operation and is a good solution for applications where self-testing is not required or suitable. It is used for driving luminaires with forward voltages (Vf) of 6V to 55V, and built-in adaptability that allows for optimum output current based on the forward voltage of the specific light engine for a more precise match to the controlled LED scheme. Features: 3W power consumption with approx 300 lumens, Suitable for independent mounting, Auto load detecting, Compatible with leading brands of mains drivers, SmartCharge technology for NiMH batteries, Battery deep discharge protection, Compatible with NiMH batteries, 3-hour rated emergency duration, SELV output. Supply current (max) 25mA. Ambient temperature (ta): 0°C to +35°C. Max case temperature (tc) +70°C. Conductor size : 0.2 to 1.5mm². NiMH battery. Product contains a charging regime that prolongs battery life and reduces parasitic power consumption during the product life cycle. By controlling battery temperature this results in energy saving and reduction in maintenance costs throughout the premises.



PRODUCT OVERVIEW

Product name	EMERGENCY PACK MANUAL TESTING 6V-55V
Technology	Accessory
General application	Education, Hospitality, Office, Retail
E-number FI	4278349
Warranty	1 year
Product EAN number	5410288466002

DATA TABLE

General data

Product name	EMERGENCY PACK MANUAL TESTING 6V-55V
Technology	Accessory
General application	Education, Hospitality, Office, Retail
E-number FI	4278349
Warranty	1 year

Physical data

Weight (kg)	0.47
-------------	------

Packaging

Single packaging type	Carton
Product EAN number	5410288466002
Packaging single length / height (cm)	28.5
Packaging single width (cm)	10.0
Packaging single depth (cm)	4.5
Units per inner package	1
Units per outer package	25
Packaging outer width (cm)	31.0
Packaging outer depth (cm)	30.0

Emergency KITS
EMERGENCY PACK MANUAL TESTING 6V-55V
0046600

Safety data	
Dry applications use only	Yes

TECHNICAL DRAWINGS

