


## Weatherproof LED G3 Accessories

WTRPRF SPARE CLIPS 10 PCS

0048879



### Product features

- 10 piece spare diffuser clips for Sylproof Superia LED G3, Hydroproof LED G3 and START Waterproof LED G3 weatherproof luminaires.



## PRODUCT OVERVIEW

|                     |                           |
|---------------------|---------------------------|
| Product name        | WTRPRF SPARE CLIPS 10 PCS |
| Technology          | Accessory                 |
| General application | Logistics & Industry      |
| Warranty            | 5 years                   |
| Product EAN number  | 5410288488790             |

## DATA TABLE

### General data

|                                  |                           |
|----------------------------------|---------------------------|
| Product name                     | WTRPRF SPARE CLIPS 10 PCS |
| Technology                       | Accessory                 |
| General application              | Logistics & Industry      |
| Operating temperature range (°C) | -20°C...+40°C             |
| Warranty                         | 5 years                   |

### Physical data

|                             |       |
|-----------------------------|-------|
| Nominal Product Length (mm) | 36    |
| Nominal Product Width (mm)  | 25    |
| Weight (kg)                 | 0.048 |

### Packaging

|                                       |               |
|---------------------------------------|---------------|
| Single packaging type                 | Plastic       |
| Product EAN number                    | 5410288488790 |
| Packaging single length / height (cm) | 22.0          |
| Packaging single width (cm)           | 15.0          |
| Packaging single depth (cm)           | 2.5           |
| Units per outer package               | 1             |
| Packaging outer width (cm)            | 15.0          |
| Packaging outer depth (cm)            | 2.5           |

### Safety data

|                                  |        |
|----------------------------------|--------|
| Optimal operating condition (°C) | -20-40 |
|----------------------------------|--------|