

Start Surface Slim IP54 - Round
START SURFACE SLIM IP54 ROUND 4000LM 2CCT D WH
0043513



Product features

- Ceiling / wall round luminaire with integrated LED. Perfect solution for corridors, circulation areas or bathrooms. Even and uniform light in a slim but robust design. Power 35W, lumen output 4000 lumens, lumen efficacy 114 lm/W, dual color temperature (3000K/4000K). Supplied with phase dimming driver (leading edge/trailing edge). Mains Voltage 220-240V~. Body Size: 400mm diameter x 53mm height. IK07, IP54 Protection rating. PC Polycarbonate Opal diffuser. Low maintenance with 58000 hours LED lifespan expectancy. Warranty: 3 years.



PRODUCT OVERVIEW

Product name	START SURFACE SLIM IP54 ROUND 4000LM 2CCT D WH
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted
General application	Hospitality
E-number FI	4278399
Warranty	3 years
Fixture luminous flux (lm)	4000
Luminaire efficacy (lm/W)	114
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM4
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	35
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP54
IK rating	IK07
Product EAN number	5410288435138

DATA TABLE

General data	
Product name	START SURFACE SLIM IP54 ROUND 4000LM 2CCT D WH
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Wall surface mounted

Start Surface Slim IP54 - Round

START SURFACE SLIM IP54 ROUND 4000LM 2CCT D WH
0043513

General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
E-number FI	4278399
Warranty	3 years

Optical data

Fixture luminous flux (lm)	4000
Luminaire efficacy (lm/W)	114
Correlated colour temperature range (K)	3000 - 4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM4
Beam Angle (°)	120
Distribution type	Diffuse
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	35
Mains voltage (V)	220-240V
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	18
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Transformer required	No
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Inrush Current (A)	7.9
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 16A B Breaker	32

Lifetime data

Lifespan L70 B50	58000
Lifespan L80 B50	37000
Lifespan L90 B50	19000

Physical data

Housing colour	White
IP rating	IP54
IK rating	IK07
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Diameter (mm)	400
Weight (kg)	1.63

Start Surface Slim IP54 - Round

START SURFACE SLIM IP54 ROUND 4000LM 2CCT D WH
0043513





Packaging

Single packaging type	Carton
Product EAN number	5410288435138
Packaging single length / height (cm)	40.5
Packaging single width (cm)	5.8
Packaging single depth (cm)	40.7
Units per outer package	4
Packaging outer width (cm)	25.5
Packaging outer depth (cm)	42.5

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

Start Surface Slim IP54 - Round

START SURFACE SLIM IP54 ROUND 4000LM 2CCT D WH

0043513

