

IP20 LED Batten - Twin
LED IP20 BATTEN L1200 TWIN 4000K
0045163



Product features
•full range of LED Battens to replace traditional T8 battens (600mm, 1200mm, 1500mm and 1800mm), ease of installation, 4000K, 25000h lifetime



PRODUCT OVERVIEW

Product name	LED IP20 BATTEN L1200 TWIN 4000K
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer
Warranty	2 years
Fixture luminous flux (lm)	3300
Luminaire efficacy (lm/W)	110
Colour temperature (K)	4000
Light colour	Neutral White
Photobiological Risk Group	RG0
Total power consumption (W)	30
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Housing colour	White
IP rating	IP20
IK rating	IK02
Product EAN number	5410288451633

DATA TABLE

General data	
Product name	LED IP20 BATTEN L1200 TWIN 4000K
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
General application	Residential & Consumer
Performance ambient temperature Tq (°C)	25
Warranty	2 years

IP20 LED Batten - Twin

LED IP20 BATTEN L 1200 TWIN 4000K
0045163

Optical data

Fixture luminous flux (lm)	3300
Luminaire efficacy (lm/W)	110
Colour temperature (K)	4000
Light colour	Neutral White
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	30
Mains voltage (V)	220-240V
Electrical protection	Class I
Control gear required	No
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	27
Max. Luminaires per 13A C Breaker	34
Max. Luminaires per 10A B Breaker	18
Max. Luminaires per 16A B Breaker	28
Max. Luminaires per 20A B Breaker	36

Lifetime data

Lifespan L70 B50	25000
------------------	-------

Physical data


Housing colour	White
IP rating	IP20
IK rating	IK02
Nominal Product Length (mm)	1200
Nominal Product Width (mm)	82
Weight (kg)	1.06

Packaging

Single packaging type	Mix blister(20% carton, 80% pl
Product EAN number	5410288451633
Packaging single length / height (cm)	120.0
Packaging single width (cm)	8.22
Packaging single depth (cm)	4.8
Units per outer package	12
Packaging outer width (cm)	22.5
Packaging outer depth (cm)	28.0

PHOTOMETRY

IP20 LED Batten - Twin
LED IP20 BATTEN L1200 TWIN 4000K
0045163



TECHNICAL DRAWINGS

