

Start Surface IP66 Ø350mm DALI
START SURFACE IP66 1500LM 840 IK10 DALI WHT
0049246



Product features

- LED exterior surface mounted luminaire, 350mm diameter, 1500lm as max. lumen output, 15W max. power consumption, 100lm/W efficacy, 4000K color temperature, CRI80, IP66, IK10, 60,000 hours (L70), white housing, vandal resistant. DALI and DALI 2 dimming compatibility, supplied with anti-theft screws



PRODUCT OVERVIEW

Product name	START SURFACE IP66 1500LM 840 IK10 DALI WHT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Hospitality
Warranty	5 years
Fixture luminous flux (lm)	1500
Luminaire efficacy (lm/W)	111
LOR (%)	100
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	120
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	14
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP66
IK rating	IK10
Product EAN number	5410288492469

DATA TABLE

Start Surface IP66 Ø350mm DALI

START SURFACE IP66 1500LM 840 IK10 DALI WHT

0049246

General data

Product name	START SURFACE IP66 1500LM 840 IK10 DALI WHT
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting
General application	Hospitality
Operating temperature range (°C)	0°C...+25°C
Performance ambient temperature T _a (°C)	25
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1500
Luminaire efficacy (lm/W)	111
LOR (%)	100
Colour temperature (K)	4000
Colour Code	840
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM6
Adjustable chromaticity	N
Beam Angle (°)	120
Glare control	< 25
Photobiological Risk Group	RG0
Lumen maintenance at end of nominal life (%)	70

Electrical data

Total power consumption (W)	14
Mains voltage (V)	220-240V
Lamp power factor	1
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Control gear mounting	Integrated
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
Inrush Current (A)	5
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	52
Max. Luminaires per 13A C Breaker	68
Max. Luminaires per 10A B Breaker	31
Max. Luminaires per 16A B Breaker	50
Max. Luminaires per 20A B Breaker	62

Start Surface IP66 Ø350mm DALI

START SURFACE IP66 1500LM 840 IK10 DALI WHT
0049246

Lifetime data

Lifespan L70 B50	60000
Lifespan L70 B10	60000
Lifespan L80 B50	60000
Lifespan L80 B10	60000
Lifespan L90 B50	42000
Lifespan L90 B10	35000


Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP66
IK rating	IK10
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Diameter (mm)	350
Weight (kg)	1.1

Packaging

Single packaging type	Carton
Product EAN number	5410288492469
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	11.0
Units per outer package	1
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	11.0

PHOTOMETRY



0.5	1.52	E(0°) E(C0)	55.7°	1945 151
1.0	3.04	E(0°) E(C0)	55.7°	486 40
1.5	4.57	E(0°) E(C0)	55.7°	216 13
2.0	6.09	E(0°) E(C0)	55.7°	122 10
2.5	7.61	E(0°) E(C0)	55.7°	78 6
3.0	9.13	E(0°) E(C0)	55.7°	54 4

Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 113.4°)

TECHNICAL DRAWINGS

Start Surface IP66 Ø350mm DALI

START SURFACE IP66 1500LM 840 IK10 DALI WHT

0049246

