

START eco Batten IP65 - NEW
START eco Batten 1500 IP65 6000lm 840
0045754



Product features

- The new upgraded START eco Batten IP65 is a versatile range of slimline LED waterproof luminaires that provide an ideal solution for applications such as workshops, garages and outdoor covered spaces. The design allows the luminaire to be easily linked to another luminaire through an IP65 rated connector. The product can be a slimline replacement for single and twin 36W/58W fluorescent waterproof battens. Polycarbonate housing and diffuser, 6000 lm, 42 W, 143 lm/W, 4000 K, drive current 95 mA, non dimmable, CRI 80, IP65, IK08, Class II, nominal average lifetime (h): 30000, 1560 mm x 80 mm x 55 mm, energy class: A++ A+ A.



PRODUCT OVERVIEW

Product name	START eco Batten 1500 IP65 6000lm 840
Technology	LED
Housing	PC Polycarbonate
General application	Residential & Consumer
E-number FI	4278238
Warranty	3 years
Fixture luminous flux (lm)	6000
Luminaire efficacy (lm/W)	143
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	120
Photobiological Risk Group	RG0
Total power consumption (W)	42
Electrical protection	Class II
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP65
IK rating	IK08
Product EAN number	5410288457543

DATA TABLE

General data	
Product name	START eco Batten 1500 IP65 6000lm 840
Technology	LED
Housing	PC Polycarbonate
General application	Residential & Consumer
Operating temperature range (°C)	-10°C...+40°C
Performance ambient temperature Tq (°C)	25

START eco Batten IP65 - NEW

START eco Batten 1500 IP65 6000lm 840
0045754

E-number FI	4278238
Warranty	3 years

Optical data

Fixture luminous flux (lm)	6000
Luminaire efficacy (lm/W)	143
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	120
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	42
Mains voltage (V)	220-240V
Lamp power factor	0.9
Electrical protection	Class II
Dimmable	No
Inrush Current (A)	50
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	12
Max. Luminaires per 13A C Breaker	15
Max. Luminaires per 10A B Breaker	8
Max. Luminaires per 16A B Breaker	12
Max. Luminaires per 20A B Breaker	16

Lifetime data

Lifespan L70 B50	50000
Lifespan L80 B50	30000

Physical data

Housing colour	White
IP rating	IP65
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	1560
Nominal Product Width (mm)	80
Weight (kg)	0.92

Packaging

Single packaging type	Carton
Product EAN number	5410288457543
Packaging single length / height (cm)	158.6
Packaging single width (cm)	8.3


START eco Batten IP65 - NEW
START eco Batten 1500 IP65 6000lm 840
0045754

Packaging single depth (cm)	5.8
Units per outer package	9
Packaging outer width (cm)	25.0
Packaging outer depth (cm)	27.0

Safety data

Optimal operating condition (°C)	-10-40
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

