


Kalani Asymmetric
Kalani IP66 6KLM 840 ASYM
0048535



Product features

- Exterior LED Floodlight, comes complete with 1500mm flying lead and adjustable bracket, aluminium housing, clear glass diffuser, IP66, IK08, Class I, 4000K, Non-dimming, 6450lm, 50W, 129lm/W, CRI80, Asymmetrical Wide beam angle (65° x 120° imax@55°), 100000 hrs L80B20 lifespan, 314 x 240 x 63mm (LxWxD) dimensions, 2.5kg weight.



PRODUCT OVERVIEW

Product name	Kalani IP66 6KLM 840 ASYM
Technology	LED
General application	Logistics & Industry
E-number FI	4579566
Warranty	5 years
Fixture luminous flux (lm)	6450
Luminaire efficacy (lm/W)	129
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	65°x120°
Photobiological Risk Group	RG1
Total power consumption (W)	50
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
IP rating	IP66
IK rating	IK08
Product EAN number	5410288485355

DATA TABLE

General data	
Product name	Kalani IP66 6KLM 840 ASYM
Technology	LED
General application	Logistics & Industry
Operating temperature range (°C)	-30°C...+50°C
Performance ambient temperature Tq (°C)	25
E-number FI	4579566
Warranty	5 years

Kalani Asymmetric

Kalani IP66 6KLM 840 ASYM
0048535

Optical data

Fixture luminous flux (lm)	6450
Luminaire efficacy (lm/W)	129
Colour temperature (K)	4000
Light colour	Neutral White
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	65*120
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	50
Mains voltage (V)	220-240V
Lamp power factor	0.95
Electrical protection	Class I
Dimmable	No
Dimming method	N/A
Inrush Current (A)	40
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	6
Max. Luminaires per 13A C Breaker	9
Max. Luminaires per 10A B Breaker	4
Max. Luminaires per 16A B Breaker	6
Max. Luminaires per 20A B Breaker	8
Mains surge immunity (differential mode - > L-N) (kV)	6
Mains surge immunity (common mode -> L/N - GND) (kV)	10

Lifetime data

Lifespan L70 B50	100000
Lifespan L80 B20	100000

Physical data

IP rating	IP66
IK rating	IK08
Nominal Product Length (mm)	314
Nominal Product Width (mm)	240
Weight (kg)	2.5

Packaging


Single packaging type	Carton
Product EAN number	5410288485355
Packaging single length / height (cm)	37.0
Packaging single width (cm)	11.0
Packaging single depth (cm)	28.0
Units per outer package	1
Packaging outer width (cm)	11.0
Packaging outer depth (cm)	28.0

Kalani Asymmetric Kalani IP66 6KLM 840 ASYM 0048535

Safety data

Optimal operating condition (°C)	-30-50
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

