

ToLEDo CANDLE V6 470LM 840 E14 SL
0027515



Features

- Compact and elegant design
- Suitable replacement for halogen, incandescent and compact fluorescent candle lamps
- Instant light at the flick of a switch
- Uniform light distribution
- Good colour rendering (CRI 80)
- Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas
- Lower maintenance costs
- A+ energy rating

Product Overview

Product name	ToLEDo CANDLE V6 470LM 840 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740659
Luminous flux (lm)	470
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Beam Angle (°)	180
Wattage (W)	5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288275154
Warranty	3 years

Data table

ToLEDo CANDLE V6 470LM 840 E14 SL 0027515

GENERAL DATA

Product name	ToLEDo CANDLE V6 470LM 840 E14 SL
Technology	LED
Watt (Rated) (W)	5
Cap/Base	E14
Fixture rating	Open
General application	Education, Hospitality, Residential & Consumer
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740659
Warranty	3 years

OPTICAL DATA

Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Beam Angle (°)	180
Lumen maintenance at end of nominal life (%)	70

ELECTRICAL DATA

Wattage (W)	5
Equivalent watt (W)	40
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
Control gear required	No

ToLEDo CANDLE V6 470LM 840 E14 SL 0027515

No. Of switching cycles before premature failures	>50000
Inrush Current (A)	3
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	138
Max. Luminaires per 16A C Breaker	222
Max. Luminaires per 20A C Breaker	278

LIFETIME DATA

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

PHYSICAL DATA

Nominal Product Length (mm)	104
Nominal Product Diameter (mm)	35
Weight (kg)	0.026

PACKAGING

Single packaging type	Carton
Product EAN number	5410288275154
Packaging single length / height (cm)	10.2
Packaging single width (cm)	3.5
Packaging single depth (cm)	3.5
DUN14 (inner)	25410288275158
Units per inner package	6
Packaging inner length / height (cm)	11.5
Packaging inner width (cm)	8.0
Packaging inner depth (cm)	11.5
DUN14 (outer)	15410288275151
Units per outer package	60
Packaging outer length / height (cm)	42.5
Packaging outer width (cm)	13.0
Packaging outer depth (cm)	25.5



ToLEDo CANDLE V6 470LM 840 E14 SL
0027515

SAFETY DATA

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures