

## RANA NEO Recessed 1200

RANA NEO 3700LM REC 1200x300 840 CC EM 1L WHITE

0052595



### Product features

- Ceiling Recessed LED Linear luminaire (lay-in), with Louvre + MPO diffuser, Direct Light Distribution, Luminaire Dimensions: 1196x296x52mm, Sylvania White body colour, IP20, IK07, Emergency 3 hours, Low LED flicker (+/-5%), Neutral White (4000K), LED Colour Temperature, 3761lm, 32W, 117lm/W, CRI>80, 3 SDCM (3-step MacAdam ellipse) LED Colour Consistency, UGR<18, Luminance at 65° < 3000 cd/m2, Lifespan: 96,000 hours L80B20, Glow Wire Test 850°C, Quick and easy electrical connection with direct access to push-connectors on top, 2 x metallic safety cables (1.5m) included, the luminaire can be covered with building insulation of Glass Wool type.



### PRODUCT OVERVIEW

|                                 |                                                 |
|---------------------------------|-------------------------------------------------|
| Product name                    | RANA NEO 3700LM REC 1200x300 840 CC EM 1L WHITE |
| Technology                      | LED (3 SDCM)                                    |
| Housing                         | Steel                                           |
| Mount                           | Ceiling recessed mounting                       |
| General application             | Education, Office                               |
| ETIM Class                      | EC002892                                        |
| Warranty                        | 5 years                                         |
| Fixture luminous flux (lm)      | 3761                                            |
| Luminous flux (lm)              | 3761                                            |
| Luminaire efficacy (lm/W)       | 117                                             |
| Colour temperature (K)          | 4000                                            |
| Light colour                    | Neutral White                                   |
| CRI (Ra)                        | 80                                              |
| Colour Variation Initial (SDCM) | SDCM3                                           |
| Glare control                   | < 18                                            |
| Photobiological Risk Group      | RG0                                             |
| Luminous flux (emergency) (lm)  | 80                                              |
| Total power consumption (W)     | 32                                              |
| Electrical protection           | Class I                                         |
| Control gear type               | LED driver constant current                     |
| Dimmable                        | No                                              |
| Dimming method                  | N/A                                             |
| LED Flickering Rate             | Ultra low (5% or less)                          |
| Housing colour                  | RAL 9016 - Traffic white / Bezel                |
| IP rating                       | IP20                                            |
| IK rating                       | IK07                                            |
| Product EAN number              | 5410288525952                                   |

### DATA TABLE

#### General data

|              |                                                 |
|--------------|-------------------------------------------------|
| Product name | RANA NEO 3700LM REC 1200x300 840 CC EM 1L WHITE |
|--------------|-------------------------------------------------|

## RANA NEO Recessed 1200

*RANA NEO 3700LM REC 1200x300 840 CC EM 1L WHITE*  
0052595

|                                         |                           |
|-----------------------------------------|---------------------------|
| Technology                              | LED (3 SDCM)              |
| Housing                                 | Steel                     |
| Mount                                   | Ceiling recessed mounting |
| General application                     | Education, Office         |
| Performance ambient temperature Tq (°C) | 25                        |
| ETIM Class                              | EC002892                  |
| Warranty                                | 5 years                   |

### Optical data

|                                 |               |
|---------------------------------|---------------|
| Fixture luminous flux (lm)      | 3761          |
| Luminous flux (lm)              | 3761          |
| Luminaire efficacy (lm/W)       | 117           |
| Colour temperature (K)          | 4000          |
| Light colour                    | Neutral White |
| CRI (Ra)                        | 80            |
| Colour Variation Initial (SDCM) | SDCM3         |
| Glare control                   | < 18          |
| Photobiological Risk Group      | RG0           |
| Luminous flux (emergency) (lm)  | 80            |
| Emergency duration (h)          | 3             |

### Electrical data

|                                                                |                             |
|----------------------------------------------------------------|-----------------------------|
| Total power consumption (W)                                    | 32                          |
| Mains voltage (V)                                              | 220-240V                    |
| Lamp power factor                                              | 0.97                        |
| THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x % | 15                          |
| Electrical protection                                          | Class I                     |
| Control gear required                                          | No                          |
| Control gear type                                              | LED driver constant current |
| Dimmable                                                       | No                          |
| Dimming method                                                 | N/A                         |
| Drive current (mA)                                             | 300                         |
| Inrush Current (A)                                             | 5.5                         |
| Inrush Duration (µs)                                           | 20                          |
| Glow Wire Test (°C)                                            | 850                         |
| Energy Efficiency Class (A->G) of contained light source       | C                           |
| Nominal Frequency (Hz)                                         | 50/60Hz                     |
| LED Flickering Rate                                            | Ultra low (5% or less)      |
| Max. Luminaires per 10A C Breaker                              | 41                          |
| Max. Luminaires per 13A C Breaker                              | 53                          |
| Max. Luminaires per 16A C Breaker                              | 65                          |
| Max. Luminaires per 20A C Breaker                              | 82                          |
| Max. Luminaires per 10A B Breaker                              | 41                          |
| Max. Luminaires per 13A B Breaker                              | 53                          |
| Max. Luminaires per 16A B Breaker                              | 65                          |
| Max. Luminaires per 20A B Breaker                              | 82                          |

## RANA NEO Recessed 1200

*RANA NEO 3700LM REC 1200x300 840 CC EM 1L WHITE*  
0052595

### Lifetime data

|                  |        |
|------------------|--------|
| Lifespan L70 B50 | 100000 |
| Lifespan L80 B20 | 96000  |


### Physical data

|                             |                                  |
|-----------------------------|----------------------------------|
| Housing colour              | RAL 9016 - Traffic white / Bezel |
| IP rating                   | IP20                             |
| IK rating                   | IK07                             |
| Diffuser finish             | Matt/satinized                   |
| Diffuser material           | PC Polycarbonate                 |
| Nominal Product Length (mm) | 1196                             |
| Nominal Product Width (mm)  | 296                              |
| Nominal Product Height (mm) | 52                               |
| Weight (kg)                 | 5.5                              |


### Packaging

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5410288525952  |
| Packaging single length / height (cm) | 124.5          |
| Packaging single width (cm)           | 6.5            |
| Packaging single depth (cm)           | 32.0           |
| DUN14 (outer)                         | 05410288525952 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 124.5          |
| Packaging outer width (cm)            | 6.5            |
| Packaging outer depth (cm)            | 32.0           |

## PHOTOMETRY



**RANA NEO Recessed 1200**  
*RANA NEO 3700LM REC 1200x300 840 CC EM 1L WHITE*  
**0052595**



**TECHNICAL DRAWINGS**

