


START Downlight Flat IP44 Dimmable 108MM Round Recessed

Start Downlight Flat 108 IP44 600LM 840 DIM
0054119



Product features

- START Downlight Flat IP44 DIM is an integrated LED recessed downlight with a separate phase dimmable driver and Loop in out box; 7W; 600Lm; 86Lm/W; 4000K; IP44 rated from the front



PRODUCT OVERVIEW

Product name	Start Downlight Flat 108 IP44 600LM 840 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
ETIM Class	EC001744
E-number FI	4278491
Warranty	5 years
Fixture luminous flux (lm)	600
Luminaire efficacy (lm/W)	85
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	7
Electrical protection	Class II
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK06
Product EAN number	5410288541198

DATA TABLE

General data

START Downlight Flat IP44 Dimmable 108MM Round Recessed

Start Downlight Flat 108 IP44 600LM 840 DIM

0054119

Product name	Start Downlight Flat 108 IP44 600LM 840 DIM
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
E-number FI	4278491
Warranty	5 years

Optical data

Fixture luminous flux (lm)	600
Luminaire efficacy (lm/W)	85
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	120
Distribution type	Symmetric
Glare control	< 28
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	7
Mains voltage (V)	220-240V
Lamp power factor	0.9
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20.0
Electrical protection	Class II
Control gear required	No
Control gear type	LED driver constant current
Dimmable	Yes
Dimming method	Mains: leading / trailing edge
Drive current (mA)	180
Inrush Current (A)	2.35
Inrush Duration (µs)	120
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	133
Max. Luminaires per 13A C Breaker	173
Max. Luminaires per 16A C Breaker	213
Max. Luminaires per 20A C Breaker	267
Max. Luminaires per 10A B Breaker	133
Max. Luminaires per 13A B Breaker	173

START Downlight Flat IP44 Dimmable 108MM Round Recessed

Start Downlight Flat 108 IP44 600LM 840 DIM

0054119

Max. Luminaires per 16A B Breaker	213
Max. Luminaires per 20A B Breaker	267

Lifetime data

Lifespan L70 B50	78000
Lifespan L80 B20	43000
Lifespan L80 B10	42000
Lifespan L90 B10	23000

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK06
Diffuser finish	Opal
Diffuser material	PS Polystyrene
Reflector finish	None
Nominal Product Length (mm)	120
Nominal Product Width (mm)	120
Nominal Product Height (mm)	21
Nominal Product Diameter (mm)	120
Cutout Dimensions (W x L in mm or Diameter in mm)	105
Weight (kg)	0.237

Packaging

Single packaging type	Carton
Product EAN number	5410288541198
Packaging single length / height (cm)	19.5
Packaging single width (cm)	12.5
Packaging single depth (cm)	4.2
DUN14 (outer)	15410288541195
Units per outer package	15
Packaging outer length / height (cm)	39.0
Packaging outer width (cm)	23.0
Packaging outer depth (cm)	21.0

Safety data



Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY

START Downlight Flat IP44 Dimmable 108MM Round Recessed

Start Downlight Flat 108 IP44 600LM 840 DIM

0054119



TECHNICAL DRAWINGS

