

## Beacon LED XL

### BEACON XL 93CRI 3K MEDIUM BEAM L3 WHITE

### 2059683



#### Product features

- Integrated LED spotlight, white RAL 9016, compact and minimalist design, ideal for retail, display, museum and gallery applications, die-cast aluminium body, passive cooling heatsink, beam angle: 34° medium beam, optics: Polycarbonate lens, colour temperature: 3000K warm white, total system power: 33W, total fixture output: 3060lm, luminaire efficacy: 93lm/W, LOR: 100%, colour rendering: Ra 93 typical, LED Chromacity: 3 step MacAdam ellipse, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 800mA, electronic driver, non-dimmable, power factor: 0.9 electrical protection: CLASS II, 3-circuit track adaptor, suitable for Concord Lytespan 3 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø113x165x205mm, weight: 1.66kg.



#### PRODUCT OVERVIEW

|                             |                                         |
|-----------------------------|-----------------------------------------|
| Product name                | BEACON XL 93CRI 3K MEDIUM BEAM L3 WHITE |
| Technology                  | LED                                     |
| Housing                     | Aluminium                               |
| Mount                       | Track mounting                          |
| Environment                 | Internal                                |
| General application         | Museums & Galleries, Retail             |
| ETIM Class                  | EC001744                                |
| E-number FI                 | 4280843                                 |
| Warranty                    | 5 years                                 |
| Fixture luminous flux (lm)  | 3060                                    |
| Luminaire efficacy (lm/W)   | 93                                      |
| LOR (%)                     | 100                                     |
| Colour temperature (K)      | 3000                                    |
| Light colour                | Warm White                              |
| CRI (Ra)                    | 93                                      |
| Colour Consistency (SDCM)   | 3                                       |
| Beam Angle (°)              | 34                                      |
| Photobiological Risk Group  | RG1                                     |
| Total power consumption (W) | 33                                      |
| Product Voltage (V)         | 240                                     |
| Electrical protection       | Class II                                |
| Control gear type           | Electronic ballast                      |
| Dimming method              | N/A                                     |
| Housing colour              | White                                   |
| IP rating                   | IP20                                    |
| IK rating                   | IK02                                    |
| Product EAN number          | 5025768596836                           |

#### DATA TABLE

## Beacon LED XL

### BEACON XL 93CRI 3K MEDIUM BEAM L3 WHITE

### 2059683

#### General data

|                                         |                                         |
|-----------------------------------------|-----------------------------------------|
| Product name                            | BEACON XL 93CRI 3K MEDIUM BEAM L3 WHITE |
| Technology                              | LED                                     |
| Housing                                 | Aluminium                               |
| Mount                                   | Track mounting                          |
| Environment                             | Internal                                |
| General application                     | Museums & Galleries, Retail             |
| Performance ambient temperature Tq (°C) | 25                                      |
| ETIM Class                              | EC001744                                |
| E-number FI                             | 4280843                                 |
| Warranty                                | 5 years                                 |

#### Optical data

|                            |            |
|----------------------------|------------|
| Fixture luminous flux (lm) | 3060       |
| Luminaire efficacy (lm/W)  | 93         |
| LOR (%)                    | 100        |
| Colour temperature (K)     | 3000       |
| Light colour               | Warm White |
| CRI (Ra)                   | 93         |
| Colour Consistency (SDCM)  | 3          |
| Adjustable chromaticity    | N          |
| Beam Angle (°)             | 34         |
| Photobiological Risk Group | RG1        |

#### Electrical data

|                                                          |                    |
|----------------------------------------------------------|--------------------|
| Total power consumption (W)                              | 33                 |
| Mains voltage (V)                                        | 220-240V           |
| Product Voltage (V)                                      | 240                |
| Lamp power factor                                        | 0.9                |
| Electrical protection                                    | Class II           |
| Control gear type                                        | Electronic ballast |
| Transformer required                                     | Yes                |
| Dimming method                                           | N/A                |
| Drive current (mA)                                       | 800                |
| Inrush Current (A)                                       | 30                 |
| Inrush Duration (µs)                                     | 200                |
| Glow Wire Test (°C)                                      | 650                |
| Energy Efficiency Class (A->G) of contained light source | E                  |
| Nominal Frequency (Hz)                                   | 50/60Hz            |
| Max. Luminaires per 10A C Breaker                        | 12                 |
| Max. Luminaires per 16A C Breaker                        | 20                 |
| Max. Luminaires per 10A B Breaker                        | 12                 |
| Max. Luminaires per 16A B Breaker                        | 20                 |

#### Lifetime data

|                  |       |
|------------------|-------|
| Lifespan L70 B50 | 72000 |
| Lifespan L80 B20 | 72000 |
| Lifespan L90 B10 | 33000 |

## Beacon LED XL

BEACON XL 93CRI 3K MEDIUM BEAM L3 WHITE  
2059683



### Physical data

|                               |       |
|-------------------------------|-------|
| Housing colour                | White |
| IP rating                     | IP20  |
| IK rating                     | IK02  |
| Nominal Product Length (mm)   | 85    |
| Nominal Product Width (mm)    | 165   |
| Nominal Product Height (mm)   | 205   |
| Nominal Product Diameter (mm) | 113   |
| Weight (kg)                   | 1.365 |

### Packaging

|                                       |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5025768596836  |
| Packaging single length / height (cm) | 25.0           |
| Packaging single width (cm)           | 19.5           |
| Packaging single depth (cm)           | 20.0           |
| DUN14 (outer)                         | 05025768596836 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 25.0           |
| Packaging outer width (cm)            | 19.5           |
| Packaging outer depth (cm)            | 20.0           |

## PHOTOMETRY



## TECHNICAL DRAWINGS

