


Equinox LUMINATURE HUMAN CENTRIC LIGHT TUNABLE WHITE (LUMI HCL TW)

EQUINOX 165 1975 LUMI HCL TW SSC
2059953



Product features

- Equinox LUMI HCL TW is an elegant and innovative luminaire designed using the latest optical technology and Tunable White Human Centric Lighting (2700-6500K) Lumi LED chips (Colour rendering index Ra >97);. It is a high quality and efficient lighting solution for office, hospitality, and retail environments. It creates inspirational halo effects regulated by a unique adjustable optic system. It is Sylsmart dimmable downlight luminaire, For 4000K - Colour rendering index Ra >97; Melanopic Ratio MEER 0.866; Fidelity Index R 95; Gamut Index R 102, Class II, Cut out dimensions: 165mm. Low Glare UGR<19. Finish White RAL9016



PRODUCT OVERVIEW

Product name	EQUINOX 165 1975 LUMI HCL TW SSC
Technology	LED LumiNature
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Office, Retail
Warranty	5 years
Fixture luminous flux (lm)	1975
Luminaire efficacy (lm/W)	79
Colour temperature (K)	4000
Light colour	Tuneable White HCL
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	64
Glare control	< 19
Photobiological Risk Group	RG1
Total power consumption (W)	25
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Remote
Dimmable	Yes
Dimming method	SylSmart SSC
Minimum dimming level (%)	1
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Product EAN number	5025768599530

Equinox LUMINATURE HUMAN CENTRIC LIGHT TUNABLE WHITE (LUMI HCL TW)

EQUINOX 165 1975 LUMI HCL TW SSC
2059953

DATA TABLE

General data

Product name	EQUINOX 165 1975 LUMI HCL TW SSC
Technology	LED LumiNature
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Office, Retail
Operating temperature range (°C)	1°C...+25°C
Performance ambient temperature Tq (°C)	25
Warranty	5 years

Optical data

Fixture luminous flux (lm)	1975
Luminaire efficacy (lm/W)	79
Colour temperature (K)	4000
Correlated colour temperature range (K)	2700 - 6500
Light colour	Tuneable White HCL
Colour Variation Initial (SDCM)	SDCM3
Colour Consistency (SDCM)	3
Beam Angle (°)	64
Distribution type	Diffuse
Glare control	< 19
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	25
Mains voltage (V)	220-240V
Lamp power factor	0.96
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	10
Electrical protection	Class II
Control gear type	LED driver constant current
Control gear mounting	Remote
Transformer required	No
Dimmable	Yes
Dimming method	SylSmart SSC
Minimum dimming level (%)	1
Drive current - Range (mA)	500mA / 500mA
Inrush Current (A)	26.4
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	D
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	16
Max. Luminaires per 13A C Breaker	21
Max. Luminaires per 10A B Breaker	10

Equinox LUMINATURE HUMAN CENTRIC LIGHT TUNABLE WHITE (LUMI HCL TW)

EQUINOX 165 1975 LUMI HCL TW SSC

2059953

Max. Luminaires per 16A B Breaker	16
Max. Luminaires per 20A B Breaker	20

Lifetime data

Lifespan L70 B50	100000
Lifespan L70 B20	100000
Lifespan L80 B50	77500
Lifespan L80 B20	68500
Lifespan L80 B10	68500
Lifespan L90 B10	39000

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP20
IK rating	IK02
Diffuser finish	Other
Diffuser material	PMMA Acrylic
Reflector finish	None
Nominal Product Diameter (mm)	175
Cutout Dimensions (W x L in mm or Diameter in mm)	165
Weight (kg)	1.55

Packaging

Single packaging type	Carton
Product EAN number	5025768599530
Packaging single length / height (cm)	20.0
Packaging single width (cm)	25.0
Packaging single depth (cm)	20.0
Units per outer package	1
Packaging outer width (cm)	25.0
Packaging outer depth (cm)	20.0

Safety data

Optimal operating condition (°C)	1-25
----------------------------------	------

TECHNICAL DRAWINGS

