

ToLEDo Superia T8 UNIVERSAL
ToLEDo Superia T8 Universal V3 5FT 3600LM 865
0029278



Product features

- 50,000 hours average rated lifeLast 2.5 times longer than 1500mm 58W fluorescent T8 Tri-phosphor lampHigh switching cycles - 200,000XHigh lumen efficacy - 157lm/WOmni-directional light distribution and wide beam angleMinimum and maximum operating temperature: -20°C to 50°CGlass construction and polycarbonate end-capsWorks only with compatible electronic ballastMust replace the fluorescent starter with LED dummy starter when used with magnetic/ CCG ballastSuitable for direct mains operation (AC 220-240V) with single-end AC inputIdeal for factories, parking lots, supermarkets, department stores, schools and offices




PRODUCT OVERVIEW

Product name	ToLEDo Superia T8 Universal V3 5FT 3600LM 865
Technology	LED
Watt (Rated) (W)	23
Lamp shape	Tube, double-ended
Type	LED exchangeable
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940799
Warranty	5 years
Luminous flux (lm)	3600
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	160
Photobiological Risk Group	RG0
Wattage (W)	23
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292786

PHOTOMETRY



ToLEDo Superia T8 UNIVERSAL
ToLEDo Superia T8 Universal V3 5FT 3600LM 865
0029278



TECHNICAL DRAWINGS

