

Resisto Emergency


Resisto 1500 IP66 4200lm 840 EM

0010253



Product features

- Resisto, integrated LED weatherproof luminaire, with UV stabilized flat diffuser designed to achieve uniform lit appearance, optimise light output and to reduce glare. 301 stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing and diffuser - no yellow discolouration over time. 4200lm; 34W; 124lm/W; 4000K; SDCM<5; non dimmable; CRI80; IP66; IK08; Class I; 69,000hrs (L80B20) lifespan; 1500mm x 89mm x 88mm; D-mark; 3-hour maintained emergency batteries.




PRODUCT OVERVIEW

Product name	Resisto 1500 IP66 4200lm 840 EM
Technology	LED
Cap/Base	N/A
Housing	PC Polycarbonate
Mount	Ceiling surface mounting, Suspended, Wall surface mounted
General application	Logistics & Industry
ETIM Class	EC002892
E-number FI	4357073
Warranty	5 years
Fixture luminous flux (lm)	4200
Luminaire efficacy (lm/W)	124
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	5
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	110
Glare control	< 23
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	655
Luminous flux (emergency) (lm)	655
Total power consumption (W)	34
Electrical protection	Class I
Control gear type	LED driver constant current
Dimmable	No
Dimming method	N/A
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Grey
IP rating	IP66
IK rating	IK08
Product EAN number	5410288102535

Resisto Emergency
Resisto 1500 IP66 4200lm 840 EM
0010253

PHOTOMETRY



TECHNICAL DRAWINGS

