

ToLEDo NEOS T8 CCG and AC
ToLEDo T8 V4 5FT 2300LM 840 25K
0029304



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lampsOmni-directional uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubesLumen output - 2300lmHigh lumen efficacy - 105 lm/WSwitching cycles - 100,000XAverage rated life 25,000 hoursLamp length - 1500mmWide beam angleSuitable for general illumination in offices, supermarkets, department stores, parking lotsSuitable for operation with electromagnetic gears/CCG and direct mains operation (220-240V)2-Year warranty




PRODUCT OVERVIEW

Product name	ToLEDo T8 V4 5FT 2300LM 840 25K
Technology	LED
Watt (Rated) (W)	22
Lamp shape	Tube, double-ended
Type	LED exchangeable
Cap/Base	G13
Lamp finish	Opal
Fixture rating	Open
General application	Education, Logistics & Industry, Office, Residential & Consumer
ETIM Class	EC001959
E-number FI	4941323
Warranty	2 years
Luminous flux (lm)	2300
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	180
Photobiological Risk Group	RG0
Wattage (W)	22
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	25000
IP rating	IP20
Product EAN number	5410288293042

PHOTOMETRY

ToLEDo NEOS T8 CCG and AC

ToLEDo T8 V4 5FT 2300LM 840 25K
0029304



TECHNICAL DRAWINGS

