

INSAVER SLIM 175 PIR / WIDE BEZEL

Insaver Slim UGR19 175 IP44 PIR 1050lm 830 0030320



Product features

Insaver Slim is a ceiling recessed LED downlight (IP44 from the front), with integrated PIR sensor with time (up to 8 mins) and daylight lux level settings. Die-cast aluminium body, loop in loop out connector for quick installation, Non dimmable LED driver, 9W; 1050lm; 117lm/W; 3000K; UGR <19 with shallow product depth 50mm. Meets TP(a) requirements.





























PRODUCT OVERVIEW


Technology LED Cap/Base N/A Housing Aluminium Mount Ceiling recessed mounting General application Hospitality, Office, Retail ETIM Class EC001744 E-number FI 4276931 Warranty 5 years Fixture luminous flux (Im) 1050 Luminaire efficacy (Im/W) 117 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) 60 Glare control < 19	Product name	Insaver Slim UGR19 175 IP44 PIR 1050lm 830
HousingAluminiumMountCeiling recessed mountingGeneral applicationHospitality, Office, RetailETIM ClassEC001744E-number FI4276931Warranty5 yearsFixture luminous flux (Im)1050Luminaire efficacy (Im/W)117Colour temperature (K)3000Light colourWarm WhiteCRI (Ra)80Colour Variation Initial (SDCM)SDCM3Beam Angle (°)60Glare control< 19	Technology	LED
Mount Ceiling recessed mounting General application Hospitality, Office, Retail ETIM Class EC001744 E-number FI 4276931 Warranty 5 years Fixture luminous flux (Im) 1050 Luminaire efficacy (Im/W) 117 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) 60 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Class II Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Cap/Base	N/A
General application Hospitality, Office, Retail ETIM Class EC001744 E-number FI 4276931 Warranty 5 years Fixture luminous flux (Im) 1050 Luminaire efficacy (Im/W) 117 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) 60 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Class II Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Housing	Aluminium
ETIM Class EC001744 E-number FI 4276931 Warranty 5 years Fixture luminous flux (Im) 1050 Luminaire efficacy (Im/W) 117 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) 60 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Class II Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Mount	Ceiling recessed mounting
E-number FI	General application	Hospitality, Office, Retail
Warranty 5 years Fixture luminous flux (lm) 1050 Luminaire efficacy (lm/W) 117 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) 60 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Class II Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	ETIM Class	EC001744
Fixture luminous flux (Im) 1050 Luminaire efficacy (Im/W) 117 Colour temperature (K) 3000 Light colour Warm White CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) 60 Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Class II Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	E-number FI	4276931
Luminaire efficacy (Im/W) Colour temperature (K) Light colour CRI (Ra) 80 Colour Variation Initial (SDCM) Beam Angle (°) Glare control Photobiological Risk Group Total power consumption (W) Electrical protection Control gear type LED driver constant current Dimmable LED Flickering Rate Housing colour RAL 9003 - Signal white IP rating IK rating IK 77	Warranty	5 years
Colour temperature (K) Light colour Warm White CRI (Ra) 80 Colour Variation Initial (SDCM) Beam Angle (°) Glare control Photobiological Risk Group RG1 Total power consumption (W) Electrical protection Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IK rating IK07	Fixture luminous flux (lm)	1050
Light colour CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK 17	Luminaire efficacy (lm/W)	117
CRI (Ra) 80 Colour Variation Initial (SDCM) SDCM3 Beam Angle (°) 60 Glare control <19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Class II Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Colour temperature (K)	3000
Colour Variation Initial (SDCM) Beam Angle (°) Glare control Photobiological Risk Group RG1 Total power consumption (W) Electrical protection Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IK 7	Light colour	Warm White
Beam Angle (°) 60 Glare control <19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Class II Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	CRI (Ra)	80
Glare control < 19 Photobiological Risk Group RG1 Total power consumption (W) 9 Electrical protection Class II Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group Total power consumption (W) Electrical protection Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Beam Angle (°)	60
Total power consumption (W) Electrical protection Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Glare control	< 19
Electrical protection Control gear type LED driver constant current Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Photobiological Risk Group	RG1
Control gear type Dimmable No LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Total power consumption (W)	9
DimmableNoLED Flickering RateUltra low (5% or less)Housing colourRAL 9003 - Signal whiteIP ratingIP44/20IK ratingIK07	Electrical protection	Class II
LED Flickering Rate Ultra low (5% or less) Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Control gear type	LED driver constant current
Housing colour RAL 9003 - Signal white IP rating IP44/20 IK rating IK07	Dimmable	No
IP rating IP44/20 IK rating IK07	LED Flickering Rate	Ultra low (5% or less)
IK rating IK07	Housing colour	RAL 9003 - Signal white
	IP rating	IP44/20
Product EAN number 5410288303208	IK rating	IK07
	Product EAN number	5410288303208


PHOTOMETRY



INSAVER SLIM 175 PIR / WIDE BEZEL

Insaver Slim UGR19 175 IP44 PIR 1050lm 830 0030320





TECHNICAL DRAWINGS

