

ToLEDo Superia T5 ECG

ToLEDo Superia T5 ECG HO V3 5FT 5600LM 840 0029271

Product features

- 50,000 hours average rated lifetime
- Last 2.5 times longer than 80W 1449mm fluorescent tri-phosphor T5 lamp
- High switching cycles 200,000X
- High lumen efficacy
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 50°C
- Glass construction and polycarbonate end-caps
- Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast
- Works only with compatible electronic ballasts
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices
















PRODUCT OVERVIEW

| Product name | ToLEDo Superia T5 ECG HO V3 5FT 5600LM 840 |
|---------------------------------|---|
| Technology | LED |
| Watt (Rated) (W) | 37 |
| Lamp shape | Tube, double-ended |
| Туре | LED exchangeable |
| Lamp finish | Opal |
| Fixture rating | Open |
| General application | Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail |
| ETIM Class | EC001959 |
| E-number FI | 4940793 |
| Warranty | 5 years |
| Luminous flux (Im) | 5600 |
| Colour temperature (K) | 4000 |
| Light colour | Cool White |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | SDCM6 |
| Beam Angle (°) | 150 |
| Photobiological Risk Group | RG0 |
| Wattage (W) | 37 |
| Product Voltage (V) | 90 |
| Dimmable | No |
| Average life (Nominal) (h) | 50000 |
| IP rating | IP20 |
| Product EAN number | 5410288292717 |

PHOTOMETRY



ToLEDo Superia T5 ECG ToLEDo Superia T5 ECG HO V3 5FT 5600LM 840 0029271



TECHNICAL DRAWINGS

