

ToLEDo Superia T8 UNIVERSAL
ToLEDo Superia T8 Universal V3 2FT 1100LM 840
0029273



Product features

- 50,000 hours average rated life
- Last 2.5 times longer than 600mm 18W fluorescent T8 Tri-phosphor lamp
- High switching cycles - 200,000X
- High lumen efficacy - 147lm/W
- Omni-directional light distribution and wide beam angle
- Minimum and maximum operating temperature: -20°C to 50°C
- Glass construction and polycarbonate end-caps
- Works only with compatible electronic ballast
- Must replace the fluorescent starter with LED dummy starter when used with magnetic/ CCG ballast
- Suitable for direct mains operation (AC 220-240V) with single-end AC input
- Ideal for factories, parking lots, supermarkets, department stores, schools and offices




PRODUCT OVERVIEW

Product name	ToLEDo Superia T8 Universal V3 2FT 1100LM 840
Technology	LED
Watt (Rated) (W)	7.5
Lamp shape	Tube, double-ended
Type	LED exchangeable
Lamp finish	Opal
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Residential & Consumer, Retail
ETIM Class	EC001959
E-number FI	4940794
Warranty	5 years
Luminous flux (lm)	1100
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	160
Photobiological Risk Group	RG0
Wattage (W)	7.5
Product Voltage (V)	230
Dimmable	No
Average life (Nominal) (h)	50000
IP rating	IP20
Product EAN number	5410288292731

PHOTOMETRY

ToLEDo Superia T8 UNIVERSAL
ToLEDo Superia T8 Universal V3 2FT 1100LM 840
0029273



TECHNICAL DRAWINGS

