


START DOWNLIGHT IP44 205 SSC
START DOWNLIGHT 205 IP44 SSC01 1950LM 830
0030375



Product features

- Ceiling recessed LED downlight IP44 (from the front), with only 60mm product depth and 205mm cutout. Ideal replacement for 1x42W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Die-cast aluminium body, 1950LM, 20W, 98lm/W, 3000K, Driver Current: 600mA, CRI80, 74° beam angle, IP44 from the front, IK07, (HxW) 60x205mm, Class 2, 220-240V, SylSmart Standalone Scene enabled. Meets TP(a) requirements.




PRODUCT OVERVIEW

Product name	START DOWNLIGHT 205 IP44 SSC01 1950LM 830
Technology	LED
Cap/Base	N/A
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Hospitality, Retail
ETIM Class	EC001744
Warranty	5 years
Fixture luminous flux (lm)	1950
Luminous flux (lm)	1950
Luminaire efficacy (lm/W)	98
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	74
Glare control	< 25
Photobiological Risk Group	RG0
Total power consumption (W)	20
Electrical protection	Class II
Control gear type	Electronic ballast
Dimmable	Yes
Dimming method	SylSmart SSC
LED Flickering Rate	Ultra low (5% or less)
Housing colour	RAL 9003 - Signal white
IP rating	IP44/20
IK rating	IK07
Product EAN number	5410288303758

START DOWNLIGHT IP44 205 SSC
START DOWNLIGHT 205 IP44 SSC01 1950LM 830
0030375

PHOTOMETRY



TECHNICAL DRAWINGS

