


Rail & Trunk System - DALI inserts
RTS 1500MM 70W NR DALI WHITE
0042593



Product features

- RTS LED linear luminaire for industrial and commercial applications. 1500 mm lenght with narrow optics provide homogenous light distribution for aisles and focus areas. Suitable for DALI Dimming. Steel housing, White color, -25 ... +30 °C operating temperature range, 4000 K, CRI 80, 3 SDMC. 70 W power consumption, 11200 lm luminous flux, 160 lm/W efficacy, 1500 mm x 70.2 mm x 78.6 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 120,000 hours.




PRODUCT OVERVIEW

Product name	RTS 1500MM 70W NR DALI WHITE
Technology	LED
Housing	Steel
General application	Logistics & Industry
ETIM Class	EC000986
Warranty	5 years
Fixture luminous flux (lm)	11200
Luminaire efficacy (lm/W)	160
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Beam Angle (°)	36
Photobiological Risk Group	RG1
Total power consumption (W)	70
Electrical protection	Class I
Dimmable	Yes
Dimming method	DALI
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288425931

PHOTOMETRY

Rail & Trunk System - DALI inserts
RTS 1500MM 70W NR DALI WHITE
0042593



TECHNICAL DRAWINGS

