

Rail & Trunk System - Electronic
RTS 1500MM 50W 5-WIRE LEFT ASYM WHITE
0042585

Image not found.


Product features

- RTS LED linear luminaire for industrial and commercial applications. 1500 mm lenght with asymmetrical (Left) optics provide homogenous light distribution for wide, shelf areas. Steel housing, White color, -25 ... +30 °C operating temperature range, 4000 K, CRI 80, 3 SDMC. 50 W power consumption, 8000 lm luminous flux, 160 lm/W efficacy, 1500 mm x 70.2 mm x 78.6 mm (L x W x H) dimensions, IP20, IK03, 220-240 V 50/60 Hz, Class I. Lifespan L70:B50 120,000 hours.

PRODUCT OVERVIEW

Product name	RTS 1500MM 50W 5-WIRE LEFT ASYM WHITE
Technology	LED
Housing	Steel
General application	Logistics & Industry
ETIM Class	EC000986
Warranty	5 years
Fixture luminous flux (lm)	8000
Luminaire efficacy (lm/W)	160
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM3
Photobiological Risk Group	RG1
Total power consumption (W)	50
Electrical protection	Class I
Dimmable	No
Minimum dimming level (%)	100
LED Flickering Rate	Ultra low (5% or less)
Housing colour	White
IP rating	IP20
IK rating	IK03
Product EAN number	5410288425856

PHOTOMETRY





Rail & Trunk System - Electronic
RTS 1500MM 50W 5-WIRE LEFT ASYM WHITE
0042585

TECHNICAL DRAWINGS
